



NX-OD6256-5

32 Digital Outputs, Standard speed, PNP 24 VDC, 0.5 A/point, 4 A/NX Unit, MIL40 connector (not included), 30 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Digital I/O
Number of digital inputs	0
Digital input type	None
OFF/ON delay	0.5-1.0 ms
Number of digital outputs	32
Digital output type	PNP
Permitted voltage at output	20.4-28.8 V
Output current	0.5 A
Short-circuit protected outputs	✓
Connection method	1-wire
Signal processing	Free running, Standard speed, Synchronous
IO-Link master	✗
I/O connection type	MIL (plug not included)
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Communication port(s)	None
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	4
Number of COM terminals	0
Degree of protection (IP)	IP20

Product Height (unpacked)	100 mm
Product Width (unpacked)	30 mm
Product Depth (unpacked)	89.52 mm
Product Weight (unpacked)	95 g

Accessories

	G70A-ZOC16-4 DC24	Output Terminal Block for Relay or SSR, 16-point, for PNP output units
	G70V-SOC16P-1	Relay terminal, PLC Output, 16 channels, PNP, Push-in terminals
	P2RV-4-100C	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 1 m
	P2RV-4-200C	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 2 m
	P2RV-4-300C	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 3 m
	P2RVC-8ST-O-5-1	Interface unit for G2RV-SR/G3RV-ST Push-in, PLC Output, 8 channels, PNP, 30 VAC/DC, Total 2 A, Push-in
	P2RVC-8ST-O-7-1	Interface unit for G2RV-SR/G3RV-ST Screw, PLC Output, 8 channels, PNP, 30 VAC/DC, Total 2 A, Rising-up screw
	XW2D-20G6	General-purpose I/O terminal block, MIL20 socket, M3 captive screws, 20 points
	XW2D-40G6	General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points
	XW2K-40G-O32C	PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting



XW2Z-0030FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 0.3 m



XW2Z-0050FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 0.5 m



XW2Z-0100FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 1 m



XW2Z-0100FH-L01

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 1 m, cross-wired



XW2Z-0100FH-L02

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 1 m



XW2Z-0100FN-L

I/O connection cable, unshielded, MIL40 to open ends, 1 m



XW2Z-0150FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 1.5 m



XW2Z-0150FN-L

I/O connection cable, unshielded, MIL40 to open ends, 1.5 m



XW2Z-0200FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 2 m



XW2Z-0200FH-L01

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 2 m, cross-wired



XW2Z-0200FH-L02

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 2 m



XW2Z-0200FN-L

I/O connection cable, unshielded, MIL40 to open ends, 2 m



XW2Z-0300FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 3 m



XW2Z-0300FH-L02

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 3 m



XW2Z-0300FN-L

I/O connection cable, unshielded, MIL40 to open ends, 3 m



XW2Z-0500FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 5 m



XW2Z-0500FN-L

I/O connection cable, unshielded, MIL40 to open ends, 5 m



XW2Z-100K

I/O connection cable, MIL40 to MIL40, 1 m



XW2Z-100N

I/O connection cable, MIL40 to 2 x MIL20, 1 m, cross-wired



XW2Z-150K

I/O connection cable, MIL40 to MIL40, 1.5 m



XW2Z-200K

I/O connection cable, MIL40 to MIL40, 2 m



XW2Z-200N

I/O connection cable, MIL40 to 2 x MIL20, 2 m, cross-wired



XW2Z-300K

I/O connection cable, MIL40 to MIL40, 3 m



XW2Z-500K

I/O connection cable, MIL40 to MIL40, 5 m



XW2Z-500N

I/O connection cable, MIL40 to 2 x MIL20, 5 m, cross-wired



XW2Z-C50K

I/O connection cable, MIL40 to MIL40, 0.5 m



XW2Z-RO100-75-D1

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 1 m



XW2Z-RO200-175-D1

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 2.0 m and 1.75 m



XW2Z-RO75-50-D1

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 0.75 m

Downloads

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 7.5 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.84 MB



NX-series Reference Manual

EN PDF 1.09 MB



NX-series Digital I/O Unit - NX-ID/IA/OD/OC/MD Datasheet

EN PDF 4.49 MB



NX-series Digital I/O Units Users Manual

EN PDF 10.1 MB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



PLC I/O Interface Wiring System Selection Connection Guide

EN PDF 1.56 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 11.8 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 13 October, 2024. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU