



## NX-PC0020

NX I/O power connection unit, IOV, 5-24 V DC input, 16 terminals, screwless push-in connector, 12mm wide

# Specifications

I/O system	NX I/O Bus
Type of module	Power connection
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Number of IOV (V+) terminals	16
Number of IOG (V-) terminals	0
Number of FG terminals	0
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	100 g

## Accessories



### NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)



**NX-TBA162**

Replacement screwless push-in connector with 16 wiring terminals (marked A+B)

## Downloads

### CAD Library



#### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



#### IO-Link Series Brochure

EN PDF 7.5 MB



#### Machine Safety Solution Brochure

EN PDF 2.86 MB



#### NX-HAD Brochure

EN PDF 1.22 MB



#### NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units

Flyer

EN PDF 3.84 MB



#### NX-series System Unit - NX-PD/PF/PC/TBX

Datasheet

EN PDF 3.25 MB



#### NX-series System Units Users Manual

EN PDF 5.59 MB



#### Omron GX-JC0x-x EtherCAT Junction Box

EtherCAT ESI file

EN ZIP 3.36 KB



#### Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



#### PLC I/O Interface Wiring System Selection

Connection Guide

EN PDF 1.56 MB



#### Sysmac Catalogue

EN PDF 43.5 MB



#### Sysmac: A Fully Integrated Platform

Brochure

EN PDF 11.8 MB

