



R88D-GT08H

G-Series servo drive, 1~ 200 VAC, Analog/Pulse input type, 800 W

Specifications

Servo control method	Analog, Pulse train
Drive supply voltage	230 V single phase
Rated output	0.75 kW

Fits to



R88M-G75030H-BS2-D

G-Series AC servo motor, 750 W, 200 VAC, 3000 rpm, 2.4 Nm, incremental, Brake, with circular connector



R88M-G75030H-S2

G-Series AC servo motor, 750 W, 200 VAC, 3000 rpm, 2.4 Nm, incremental



R88M-G75030H-S2-D

G-Series AC servo motor, 750 W, 200 VAC, 3000 rpm, 2.4 Nm, incremental, with circular connector

R88M-G75030H-BS2

G-Series AC servo motor, 750 W, 200 VAC, 3000 rpm, 2.4 Nm, incremental, Brake



R88M-G75030T-S2


G-Series AC servo motor, 750 W, 200 VAC, 3000 rpm, 2.4 Nm, absolute

Accessories

R88A-FIK107-SE

G/G5 series RFI filter; 6.6 A, 230 VAC, for 750 W models

CAD Library



G-Series Servo Drives & Motors with A/P Users Manual

EN PDF 11.1 MB



G-Series Servo Drives & Motors with MECHATROLINK-II Users Manual

EN PDF 6.23 MB



G-Series Servo Systems Brochure

EN PDF 2.57 MB



Motor Sizing Tool Operation Manual

EN PDF 3.83 MB




R88D-G, R88M-G Discontinuation Notice

EN PDF 8.04 MB



R88D-G_G-Series Servo Drive Datasheet

EN PDF 1.96 MB



motor_sizing_tool_v1.80.1.16 Configurator

EN ZIP 36.1 MB