



R88M-G10030H-S2

G-Series/SmartStep 2 AC servo motor (cylinder type), 100 W, 200 VAC, 3000 rpm, 0.32 Nm

Specifications

Servo control method	Analog, MECHATROLINK II, Pulse train
Drive supply voltage	230 V single phase
Rated output	0.1 kW
Rated speed	3000 r/min
Rated torque	0.32 Nm
Peak torque	0.9 Nm
Encoder type	Incremental
Encoder resolution	13 Bit
Motor with brake	✘
Motor with oil seal	✘
Flange size square (LC)	40 mm
Shaft diameter	8 mm
Shaft with key	✔
Shaft with tap	✔
Product Weight (unpacked)	500 g



R7D-BP01H

SmartStep 2 servo drive, pulse input type, 100 W, 1~200 VAC



R88D-GN01H-ML2

G-Series servo drive, 1~200 VAC, MECHATROLINK II integrated, 100 W




R88D-GT01H

G-Series servo drive, 1~200 VAC, Analog/Pulse input type, 100 W

Downloads

CAD Library



G-Series Servo Drives & Motors with A/P Users Manual

EN PDF 11.1 MB



G-Series Servo Drives & Motors with MECHATROLINK-II Users Manual

EN PDF 6.23 MB



G-Series Servo Systems Brochure

EN PDF 2.57 MB



Motor Sizing Tool Operation Manual

EN PDF 3.83 MB



R88D-G, R88M-G Discontinuation Notice

EN PDF 8.04 MB



R88M-G G-Series Servo Motors Datasheet

EN PDF 570 KB



SmartStep 2 Servo Drives & Motors Users Manual

EN PDF 4.27 MB



SmartStep 2 Servo System Brochure

EN PDF 3.45 MB



motor_sizing_tool_v1.80.1.16 Configurator

EN ZIP 36.1 MB

