



## R88M-G75030H-S2

G-Series AC servo motor, 750 W, 200 VAC, 3000 rpm, 2.4 Nm, incremental

# Specifications

Servo control method	Analog, MECHATROLINK II, Pulse train
Drive supply voltage	230 V single phase
Rated output	0.75 kW
Rated speed	3000 r/min
Rated torque	2.4 Nm
Peak torque	7.05 Nm
Encoder type	Incremental
Encoder resolution	13 Bit
Motor with brake	✘
Motor with oil seal	✘
Flange size square (LC)	80 mm
Shaft diameter	19 mm
Shaft with key	✔
Shaft with tap	✔
Product Weight (unpacked)	2300 g



**R88D-GN08H-ML2**  
G-Series servo drive, 1~200 VAC, MECHATROLINK II integrated, 750 W




**R88D-GP08H**  
G-Series Servo Drive, Pulse input type, 800 W, 1~200 VAC



**R88D-GT08H**  
G-Series servo drive, 1~200 VAC, Analog/Pulse input type, 800 W

## Downloads

### CAD Library



**G-Series Servo Drives & Motors with A/P Users Manual**  
EN PDF 11.1 MB



**G-Series Servo Drives & Motors with MECHATROLINK-II Users Manual**  
EN PDF 6.23 MB



**G-Series Servo Systems Brochure**  
EN PDF 2.57 MB



**Motor Sizing Tool Operation Manual**  
EN PDF 3.83 MB



**R88D-G, R88M-G Discontinuation Notice**  
EN PDF 8.04 MB



**R88M-G G-Series Servo Motors Datasheet**  
EN PDF 570 KB



**SmartStep 2 Servo Drives & Motors Users Manual**  
EN PDF 4.27 MB



**SmartStep 2 Servo System Brochure**  
EN PDF 3.45 MB



**motor\_sizing\_tool\_v1.80.1.16 Configurator**  
EN ZIP 36.1 MB

