

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 41 A, number of connections: 2, number of positions: 1, connection method: Screw connection, Rated cross section: 6 mm<sup>2</sup>, cross section: 0.2 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: red

## Commercial data

Item number	0719223
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE1
Product key	BE1211
GTIN	4017918955052
Weight per piece (including packing)	13.53 g
Weight per piece (excluding packing)	13.076 g
Customs tariff number	85369010
Country of origin	CN

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

## Technical data

### Product properties

Product type	Feed-through terminal block
Number of positions	1
Number of connections	2
Number of rows	1

### Data management status

Article revision	10
------------------	----

### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

### Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.31 W

### Connection data

Number of connections per level	2
Nominal cross section	6 mm <sup>2</sup>

### Level 1 above 1 below 1

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	10 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 10 mm <sup>2</sup>
Cross section AWG	24 ... 8 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Conductor cross section, flexible [AWG]	24 ... 10 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Cross-section with insertion bridge, rigid	4 mm <sup>2</sup>
Cross-section with insertion bridge, flexible	4 mm <sup>2</sup>
2 conductors with same cross section, solid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
2 conductors with same cross section, flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Nominal current	41 A
Maximum load current	57 A (with 10 mm <sup>2</sup> conductor cross section)

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

Nominal voltage	800 V
Nominal cross section	6 mm <sup>2</sup>

## Ex data

### Rated data (ATEX/IECEX)

Identification	⊕ II 2 GD Ex eb IIC Gb
Operating temperature range	-60 °C ... 110 °C
Ex-certified accessories	3003020 D-UK 4/10
	3006027 D-UK 16
	3003224 ATP-UK
	1205066 SZS 1,0X4,0 VDE
	1201442 E/UK
List of bridges	Fixed bridge / FB 2- 8-EX / 3029224
	Fixed bridge / FB 10- 8-EX / 3003185
Bridge data	37.5 A / 6 mm <sup>2</sup>
List of bridges	Fixed bridge / FBI 10- 8-EX / 0711700
Bridge data	39.5 A / 6 mm <sup>2</sup>
Ex temperature increase	40 K (47 A / 6 mm <sup>2</sup> )
Rated voltage	690 V
for bridging with bridge	690 V
Rated insulation voltage	630 V
output	(Permanent)

### Ex level General

Rated current	41 A
Maximum load current	51 A
Contact resistance	0.16 mΩ

### Ex connection data General

Torque range	1.5 Nm ... 1.8 Nm
Nominal cross section	6 mm <sup>2</sup>
Rated cross section AWG	10
Connection capacity rigid	0.2 mm <sup>2</sup> ... 10 mm <sup>2</sup>
Connection capacity AWG	24 ... 8
Connection capacity flexible	0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Connection capacity AWG	24 ... 10
2 conductors with same cross section, solid	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
2 conductors with the same cross-section AWG rigid	24 ... 16
2 conductors with same cross section, stranded	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
2 conductors with the same cross-section AWG flexible	24 ... 16

## Dimensions

Width	8.2 mm
End cover width	1.8 mm
Height	42.5 mm

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

Depth on NS 32	52 mm
Depth on NS 35/7,5	47 mm
Depth on NS 35/15	54.5 mm

## Material specifications

Color	red
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

## Electrical tests

### Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

### Temperature-rise test

Requirement temperature-rise test	Increase in temperature $\leq 45$ K
Result	Test passed
Short-time withstand current 6 mm <sup>2</sup>	0.72 kA
Result	Test passed

## Mechanical properties

### Mechanical data

Open side panel	Yes
-----------------	-----

## Mechanical tests

### Mechanical strength

Result	Test passed
--------	-------------

### Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	5 N
Result	Test passed

## Environmental and real-life conditions

### Needle-flame test

Time of exposure	30 s
Result	Test passed

### Ambient conditions

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

## Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

## Mounting

Mounting type	NS 35/7,5
	NS 35/15

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## Drawings

### Circuit diagram



# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/0719223>

<b>DNV</b> Approval ID: TAE00001CT				
---------------------------------------	--	--	--	--

<b>CSA</b> Approval ID: 13631				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
	600 V	50 A	26 - 8	-

<b>IECEE CB Scheme</b> Approval ID: NL-65053				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
	800 V	41 A	-	- 6

<b>EAC</b> Approval ID: RU C-DE.BL08.B.00534				
---	--	--	--	--

<b>cULus Recognized</b> Approval ID: E60425				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Use group B				
	600 V	50 A	26 - 8	-
Multi-conductor connection	600 V	50 A	18 - 12	-
Use group C				
	600 V	50 A	26 - 8	-
Multi-conductor connection	600 V	50 A	18 - 12	-
Use group F				
	800 V	50 A	26 - 8	-
Multi-conductor connection	800 V	50 A	18 - 12	-


<b>KEMA-KEUR</b> Approval ID: 71-119849				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
	800 V	41 A	-	- 6


# UK 6 N RD - Feed-through terminal block




0719223

<https://www.phoenixcontact.com/in/products/0719223>


 <b>LR</b> Approval ID: 96/20013				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
	800 V	41 A	-	- 6

 <b>NK</b> Approval ID: 09 ME 141				
---	--	--	--	--


 <b>ATEX</b> Approval ID: KEMA98ATEX1651U				
---	--	--	--	--


 <b>cUL Recognized</b> Approval ID: E192998				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
	600 V	50 A	26 - 8	-


 <b>EAC Ex</b> Approval ID: RU C-DE.HA91.B.00066				
--	--	--	--	--

 <b>GL</b> Approval ID: 98876-96 HH				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
EEx e II part certificate	690 V	43.5 A	-	- 6

 <b>IECEX</b> Approval ID: IECEX KEM 06.0034U				
---	--	--	--	--

 <b>UL Recognized</b> Approval ID: E192998				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
	600 V	50 A	26 - 8	-

 <b>CCC</b> Approval ID: 2020322313000623				
---	--	--	--	--

 <b>DNV GL-EX</b> Approval ID: TAE00003K6				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$



# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

Ex e II part certificate	440 V	32 A	-	- 2.5
--------------------------	-------	------	---	-------

**cULus Recognized**

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

## Classifications

### ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

### ETIM

ETIM 9.0	EC000897
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC


REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	32b2baed-44a6-4dde-9462-9a13d9c713cb

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>

## Accessories

 Note: Applying some accessories below might limit this product.


### SB 2- 8/13 N - Switching jumper

0200062

<https://www.phoenixcontact.com/in/products/0200062>



Switching jumper, pitch: 13 mm, number of positions: 2, color: silver

 Max. current carrying capacity: 40 A

---

### ISSBI 10- 8 - Bridge

0301534

<https://www.phoenixcontact.com/in/products/0301534>



Bridge, pitch: 8 mm, number of positions: 10, color: silver

 Max. current carrying capacity: 57 A

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## FBI 2- 8 - Fixed bridge

0200020

<https://www.phoenixcontact.com/in/products/0200020>



Fixed bridge, pitch: 8 mm, number of positions: 2, color: silver

 Max. current carrying capacity: 57 A

---


## FBI 3- 8 - Fixed bridge

0200059

<https://www.phoenixcontact.com/in/products/0200059>



Fixed bridge, pitch: 8 mm, number of positions: 3, color: silver

 Max. current carrying capacity: 57 A

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>




## FBI 4- 8 - Fixed bridge

0200046

<https://www.phoenixcontact.com/in/products/0200046>



Fixed bridge, pitch: 8 mm, number of positions: 4, color: silver

 Max. current carrying capacity: 57 A

---


## FBI 10- 8 - Fixed bridge

0203263

<https://www.phoenixcontact.com/in/products/0203263>



Fixed bridge, pitch: 8 mm, number of positions: 10, color: silver

 Max. current carrying capacity: 57 A

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>




## FBI 10- 8-EX - Fixed bridge

0711700

<https://www.phoenixcontact.com/in/products/0711700>



Fixed bridge, pitch: 8 mm, number of positions: 10, color: silver

 Max. current carrying capacity: 57 A

---


## FB 2- 8-EX - Fixed bridge

3029224

<https://www.phoenixcontact.com/in/products/3029224>



Fixed bridge, pitch: 8 mm, number of positions: 2, color: silver

 Max. current carrying capacity: 57 A

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>




## FB 4- 8 - Fixed bridge

0202183

<https://www.phoenixcontact.com/in/products/0202183>



Fixed bridge, number of positions: 4, color: silver

 Max. current carrying capacity: 57 A

---

## FB 10- 8 - Fixed bridge

0202170

<https://www.phoenixcontact.com/in/products/0202170>



Fixed bridge, pitch: 8 mm, number of positions: 10, color: silver

 Max. current carrying capacity: 57 A



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>




## FB 10- 8-EX - Fixed bridge

3003185

<https://www.phoenixcontact.com/in/products/3003185>

Fixed bridge, pitch: 8 mm, number of positions: 10, color: silver



 Max. current carrying capacity: 57 A

---

## EB 2- 8 - Insertion bridge

0202154

<https://www.phoenixcontact.com/in/products/0202154>

Insertion bridge, pitch: 8 mm, number of positions: 2, color: gray



 Max. current carrying capacity: 57 A

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>

## EB 3- 8 - Insertion bridge

0202141

<https://www.phoenixcontact.com/in/products/0202141>



Insertion bridge, pitch: 8 mm, number of positions: 3, color: gray

 Max. current carrying capacity: 57 A

---


## EB 4- 8 - Insertion bridge

0202142

<https://www.phoenixcontact.com/in/products/0202142>



Insertion bridge, pitch: 8 mm, number of positions: 4, color: gray

 Max. current carrying capacity: 57 A

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>




## EB 10- 8 - Insertion bridge

0202138

<https://www.phoenixcontact.com/in/products/0202138>

Insertion bridge, pitch: 8 mm, number of positions: 10, color: gray



 Max. current carrying capacity: 57 A

---


## EB 1/3/5/7-8 - Insertion bridge

3072340

<https://www.phoenixcontact.com/in/products/3072340>

Insertion bridge, pitch: 16.4 mm, number of positions: 4, pin assignment: 1, 3, 5, 7, length: 24 mm, color: gray



 Max. current carrying capacity: 57 A

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>




## EB 1/3/5-8 - Insertion bridge

3072341

<https://www.phoenixcontact.com/in/products/3072341>



Insertion bridge, pitch: 16.4 mm, number of positions: 3, pin assignment: 1,3,5, length: 24 mm, color: gray

 Max. current carrying capacity: 57 A

---

## WS 5- 8 - Warning label

1004416

<https://www.phoenixcontact.com/in/products/1004416>

Warning plate, with 2 plastic screws, across 5 terminal blocks, pitch 8 mm



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>

## WS 4- 8 - Warning label

1004212

<https://www.phoenixcontact.com/in/products/1004212>

Warning plate, with 2 plastic screws, across 4 terminal blocks, pitch 8 mm



---

## WS 3- 8 - Warning label

1004128

<https://www.phoenixcontact.com/in/products/1004128>

Warning plate, with 2 plastic screws, across 3 terminal blocks, pitch 8 mm



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## SCP 2-8 - Short-circuit connector

3070402

<https://www.phoenixcontact.com/in/products/3070402>



Short-circuit connector, pitch: 8.15 mm, number of positions: 2, color: orange

---

## TS-K - Separating plate

1302215

<https://www.phoenixcontact.com/in/products/1302215>



Separating plate, depth: 22 mm, width: 0.5 mm, height: 22 mm, color: gray

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

## ATP-UK - Partition plate

3003224

<https://www.phoenixcontact.com/in/products/3003224>



Partition plate, depth: 45.7 mm, width: 1.5 mm, height: 56 mm, color: gray

---

## SBS 8:UNBEDRUCKT - Marker card

1007235

<https://www.phoenixcontact.com/in/products/1007235>



Marker card, Card, white, unlabeled, can be labeled with: Marker pen, mounting type: snap into tall marker groove, snap into flat marker groove, for terminal block width: 8 mm, lettering field size: 6 x 8.1 mm

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## IS-K 10 - Bridge bar isolator

1303337

<https://www.phoenixcontact.com/in/products/1303337>



Bridge bar isolator, color: gray

---

## NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/in/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/in/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

---

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/in/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/in/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/in/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/in/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/in/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/in/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/in/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/in/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/in/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/in/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/in/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/in/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

---

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/in/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/in/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/in/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/in/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/in/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/in/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/in/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>

## ZB 8:UNBEDRUCKT - Zack marker strip

1052002

<https://www.phoenixcontact.com/in/products/1052002>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

---

## ZB 8 CUS - Zack marker strip

0825011

<https://www.phoenixcontact.com/in/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

# UK 6 N RD - Feed-through terminal block



0719223

<https://www.phoenixcontact.com/in/products/0719223>

## UC-TM 8 - Marker for terminal blocks

0818072

<https://www.phoenixcontact.com/in/products/0818072>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

---

## UC-TM 8 CUS - Marker for terminal blocks

0824597

<https://www.phoenixcontact.com/in/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>

## UCT-TM 8 - Marker for terminal blocks

0828740

<https://www.phoenixcontact.com/in/products/0828740>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

---

## UCT-TM 8 CUS - Marker for terminal blocks

0829616

<https://www.phoenixcontact.com/in/products/0829616>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>

## ZB 8,LGS:FORTL.ZAHLEN - Zack marker strip

1052015

<https://www.phoenixcontact.com/in/products/1052015>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10. 5 x 8.15 mm, Number of individual labels: 10

---

## ZB 8,QR:FORTL.ZAHLEN - Zack marker strip

1052028

<https://www.phoenixcontact.com/in/products/1052028>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10. 5 x 8.15 mm, Number of individual labels: 10

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

<https://www.phoenixcontact.com/in/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

---

## PS-MT - Test plug

0311647

<https://www.phoenixcontact.com/in/products/0311647>



Test plug, number of positions: 1, color: silver

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>

## PS-IH WH - Insulating sleeve

0311566

<https://www.phoenixcontact.com/in/products/0311566>



Insulating sleeve, number of positions: 1, color: white

---

## PS-IH RD - Insulating sleeve

0311579

<https://www.phoenixcontact.com/in/products/0311579>



Insulating sleeve, number of positions: 1, color: red



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## PS-IH BU - Insulating sleeve

0311582

<https://www.phoenixcontact.com/in/products/0311582>



Insulating sleeve, number of positions: 1, color: blue

---

## PS-IH YE - Insulating sleeve

0311595

<https://www.phoenixcontact.com/in/products/0311595>



Insulating sleeve, number of positions: 1, color: yellow

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## PS-IH GN - Insulating sleeve

0311605

<https://www.phoenixcontact.com/in/products/0311605>



Insulating sleeve, number of positions: 1, color: green

---

## PS-IH GY - Insulating sleeve

0311621

<https://www.phoenixcontact.com/in/products/0311621>



Insulating sleeve, number of positions: 1, color: gray

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## PS-IH BK - Insulating sleeve

0311634

<https://www.phoenixcontact.com/in/products/0311634>



Insulating sleeve, number of positions: 1, color: black

---

## PS-IH VT - Insulating sleeve

0311618

<https://www.phoenixcontact.com/in/products/0311618>



Insulating sleeve, number of positions: 1, color: violet

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>

## CLIPFIX 35 - End bracket

3022218

<https://www.phoenixcontact.com/in/products/3022218>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

---

## CLIPFIX 35-5 - End bracket

3022276

<https://www.phoenixcontact.com/in/products/3022276>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## E/NS 35 N - End bracket

0800886

<https://www.phoenixcontact.com/in/products/0800886>

End clamp, width: 9.5 mm, color: gray



---

## E/UK - End bracket

1201442

<https://www.phoenixcontact.com/in/products/1201442>

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray



## UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## E/UK 1 - End bracket

1201413

<https://www.phoenixcontact.com/in/products/1201413>



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

---

## PSBJ 4/15/6 FARBLOS - Test plug strip

0303419

<https://www.phoenixcontact.com/in/products/0303419>



Test plug strip, number of positions: 1, color: transparent

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## PSBJ 4/15/6 WH - Test plug strip

0303312

<https://www.phoenixcontact.com/in/products/0303312>



Test plug strip, number of positions: 1, color: white

---

## PSBJ 4/15/6 RD - Test plug strip

0303325

<https://www.phoenixcontact.com/in/products/0303325>



Test plug strip, number of positions: 1, color: red

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## PSBJ 4/15/6 BU - Test plug strip

0303354

<https://www.phoenixcontact.com/in/products/0303354>



Test plug strip, number of positions: 1, color: blue

---

## PSBJ 4/15/6 YE - Test plug strip

0303367

<https://www.phoenixcontact.com/in/products/0303367>



Test plug strip, number of positions: 1, color: yellow



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## PSBJ 4/15/6 GN - Test plug strip

0303370

<https://www.phoenixcontact.com/in/products/0303370>



Test plug strip, number of positions: 1, color: green

---

## PSBJ 4/15/6 VT - Test plug strip

0303383

<https://www.phoenixcontact.com/in/products/0303383>



Test plug strip, number of positions: 1, color: violet

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## PSBJ 4/15/6 GY - Test plug strip

0303396

<https://www.phoenixcontact.com/in/products/0303396>



Test plug strip, number of positions: 1, color: gray

---

## PSBJ 4/15/6 BK - Test plug strip

0303406

<https://www.phoenixcontact.com/in/products/0303406>



Test plug strip, number of positions: 1, color: black

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## PSB 4/7/6 - Test plug strip

0303299

<https://www.phoenixcontact.com/in/products/0303299>



Test plug strip, number of positions: 1, color: silver

---

## D-UK 4/10 - End cover

3003020

<https://www.phoenixcontact.com/in/products/3003020>



End cover, depth: 35.9 mm, width: 1.8 mm, height: 42.5 mm, color: gray

# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## EA 5-WS - Cover

1024085

<https://www.phoenixcontact.com/in/products/1024085>

Single covers, for covering one terminal block, with black symbol (lightning flash)  
snap fit, color: transparent/yellow



---

## EA 5 - Cover

1024014

<https://www.phoenixcontact.com/in/products/1024014>

Cover, material: ABS, color: transparent



# UK 6 N RD - Feed-through terminal block

0719223

<https://www.phoenixcontact.com/in/products/0719223>



## SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/in/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)