

US-WMTB (24X5) - Cable marker



0828771

<https://www.phoenixcontact.com/in/products/0828771>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable marker, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: Assembly with cable ties, cable diameter: > 13 mm, lettering field size: 24 x 5 mm, Number of individual labels: 35



Your advantages

- The markers, which are supplied as uniform cards, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- The US-WMTB... UniSheet labeling range includes markers that can be secured using standard cable binders
- The perforated marking strips are easy to separate and can be easily fitted
- The cards provide space for including function texts

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 0828771 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BG2 |
| Product key | BG2319 |
| Catalog page | Page 214 (C-3-2019) |
| GTIN | 4046356559874 |
| Weight per piece (including packing) | 12.66 g |
| Weight per piece (excluding packing) | 11 g |
| Customs tariff number | 39204910 |
| Country of origin | DE |

US-WMTB (24X5) - Cable marker



0828771

<https://www.phoenixcontact.com/in/products/0828771>

Technical data

Product properties

| | |
|--------------|-------------------|
| Product type | Conductor marking |
| Type | Card form |

Data management status

| | |
|------------------|----|
| Article revision | 00 |
|------------------|----|

Marking

| | |
|-------------------------------------|---------------------------------------|
| Number of individual labels | 35 |
| Number of individual labels per row | 7 |
| Identification technology | Thermal transfer for sheets and cards |

Dimensions

| | |
|-------------------|----------|
| Width | 14 mm |
| Text field width | 24.00 mm |
| Text field height | 5.00 mm |
| Length | 24 mm |

External dimensions

| | |
|------------------|--------------------|
| Outside diameter | > 13 mm ... 136 mm |
|------------------|--------------------|

Material specifications

| | |
|--|---------------|
| Color | white |
| Material | PVC |
| Flammability rating according to UL 94 | V0 |
| Components | Silicone-free |

Cable/line

| | |
|-------------------------|------------|
| External cable diameter | > 13.00 mm |
|-------------------------|------------|

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

Wipe resistance of inscriptions

| | |
|--------------------------------|--|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropyl [CAS No. 67-63-0] | Test passed |

US-WMTB (24X5) - Cable marker



0828771

<https://www.phoenixcontact.com/in/products/0828771>

| | |
|---|-------------|
| n-Hexane [CAS No. 110-54-3] | Test passed |
| Water + Petroleum ether [CAS No. 64742-82-1] | Test passed |

Testing in a condensation changing climate in the presence of sulfur dioxide

| | |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result | Test passed |
| Climate level | AHT 1.0 S |
| Cycles | 2 |

Salt spray test

| | |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result | Test passed |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -30 °C ... 80 °C |
| Recommended storage conditions | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |
| Shelf life | 12 months |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Mounting

| | |
|---------------|--------------------------|
| Mounting type | Assembly with cable ties |
|---------------|--------------------------|

US-WMTB (24X5) - Cable marker



0828771

<https://www.phoenixcontact.com/in/products/0828771>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281102 |
| ECLASS-12.0 | 27281102 |
| ECLASS-13.0 | 27281102 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001530 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

US-WMTB (24X5) - Cable marker



0828771

<https://www.phoenixcontact.com/in/products/0828771>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



Accessories

THERMOMARK CARD 2.0 - Thermal transfer printer

1085267

<https://www.phoenixcontact.com/in/products/1085267>



Thermal transfer printer for card materials, including Euro/US power cable and USB cable. User manual printed in German and English. Magazine for UCT-TM.. sheets and magazines for US-... cards. One packing unit each UCT-TM 6, US-EMLP (85,6x54), ink ribbon = 50 m

BLUEMARK ID - Printer

1003334

<https://www.phoenixcontact.com/in/products/1003334>



Monochrome printer with UV inkjet technology and integrated "MARKING system app" identification software. 7" touch color display for printing plastic labels in UC, UCT, US, and UM format, as well as metal labels.

US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



BLUEMARK ID COLOR - Printer

1002329

<https://www.phoenixcontact.com/in/products/1002329>



CMYK multicolor printer with UV inkjet technology, with integrated "MARKING system app" identification software, 7" touch color display for printing plastic labels in UC, UCT, and UM format, as well as metal labels.

THERMOMARK-RIBBON 110/50-TC - Ink ribbon

0801384

<https://www.phoenixcontact.com/in/products/0801384>



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 50 m, roll length: 50 m, width: 110 mm, color: black

US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



THERMOMARK-RIBBON 110-TC - Ink ribbon

0801371

<https://www.phoenixcontact.com/in/products/0801371>



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 300 m, roll length: 300 m, width: 110 mm, color: black

TMP-RIBBON 110 BK 100 - Ink ribbon cartridge

0803374

<https://www.phoenixcontact.com/in/products/0803374>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups UCT. ..., US..., and UM..., length: 70 m, roll length: 70 m, width: 110 mm, color: black

US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>

TMP-RIBBON 110 BK 101 - Ink ribbon cartridge

0803714

<https://www.phoenixcontact.com/in/products/0803714>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)..., US-TM(F)L..., US-WMTB..., US-EML..., US-EML(S)P..., US-EMLP-HA..., US-EM(S)P..., US-EML-RS..., length: 60 m, roll length: 60 m, width: 110 mm, color: black

TMP-RIBBON 110 BU 100 - Ink ribbon cartridge

0803378

<https://www.phoenixcontact.com/in/products/0803378>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)..., US-TM(F)L..., US-WMTB..., US-EML..., US-EML(S)P..., US-EMLP-HA..., US-EM(S)P..., US-EML-RS..., length: 60 m, roll length: 60 m, width: 110 mm, color: blue

US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>

TMP-RIBBON 110 GN 100 - Ink ribbon cartridge

0803380

<https://www.phoenixcontact.com/in/products/0803380>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)..., US-TM(F)L..., US-WMTB..., US-EML..., US-EML(S)P..., US-EMLP-HA..., US-EM(S)P..., US-EML-RS..., length: 60 m, roll length: 60 m, width: 110 mm, color: green

TMP-RIBBON 110 RD 100 - Ink ribbon cartridge

0803377

<https://www.phoenixcontact.com/in/products/0803377>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)..., US-TM(F)L..., US-WMTB..., US-EML..., US-EML(S)P..., US-EMLP-HA..., US-EM(S)P..., US-EML-RS..., length: 60 m, roll length: 60 m, width: 110 mm, color: red

US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



TMP-RIBBON 110 YE 100 - Ink ribbon cartridge

0803379

<https://www.phoenixcontact.com/in/products/0803379>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)..., US-TM(F)L..., US-WMTB..., US-EML..., US-EML(S)P..., US-EMLP-HA..., US-EM(S)P..., US-EML-RS..., length: 60 m, roll length: 60 m, width: 110 mm, color: yellow

BM ID-CARTR. BK - Ink cartridge

1044345

<https://www.phoenixcontact.com/in/products/1044345>



Replacement UV fluid, 23 ml, color: black

US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



BM ID-CARTR. CY - Ink cartridge

1044346

<https://www.phoenixcontact.com/in/products/1044346>

Replacement UV fluid, 23 ml, color: cyan



BM ID-CARTR. MA - Ink cartridge

1044347

<https://www.phoenixcontact.com/in/products/1044347>

Replacement UV fluid, 23 ml, color: magenta



US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



BM ID-CARTR. YE - Ink cartridge

1044348

<https://www.phoenixcontact.com/in/products/1044348>

Replacement UV fluid, 23 ml, color: yellow



TMP-US-MAG1 - Magazine

0803341

<https://www.phoenixcontact.com/in/products/0803341>

Magazine, For THERMOMARK CARD and THERMOMARK PRIME, for accommodating US cards, length: 0.166 m, width: 114 mm, height: 10 mm



US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



BM ID-ADAPTER PLATE-US - Magazine

1044355

<https://www.phoenixcontact.com/in/products/1044355>

Adapter plate for accommodating US sheets



THERMOMARK CARD - Thermal transfer printer

5146464

<https://www.phoenixcontact.com/in/products/5146464>

Thermal transfer printer for cards



US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



THERMOMARK PRIME - Thermal transfer printer

5148888

<https://www.phoenixcontact.com/in/products/5148888>



Mobile thermal transfer printer for card materials, including power supply unit, Euro/US power cable, and USB cable. User manual printed in German and English. Magazine for UCT-TM... sheets and magazine for US-... cards. One packing unit each UCT-TM 6, US-EMLP (85,6x54), ink ribbon cartridge = 70 m

BLUEMARK CLED - Printer

5147999

<https://www.phoenixcontact.com/in/products/5147999>



Printers with LED-UV technology for printing plastic labels in UniCard format.

US-WMTB (24X5) - Cable marker

0828771

<https://www.phoenixcontact.com/in/products/0828771>



THERMOMARK CARD-US-MAG1 - Magazine

5146451

<https://www.phoenixcontact.com/in/products/5146451>

Magazine for the THERMOMARK CARD printer, for accommodating US cards



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in