0829484

https://www.phoenixcontact.com/in/products/0829484



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 2.95 x 10.5 mm, Number of individual labels: 102

Your advantages

- The UCT-TM... UniCard labeling range includes markers for Phoenix Contact products with tall marker grooves, e.g. terminals
- · The markers, which are supplied in uniform sheets, can be marked quickly, easily, and precisely using the card printers
- The sheets provide additional space for project information and function text that can be helpful during further assembly
- · The multi-section marking strips are easy to fit and can be easily separated if required
- · Marking service: Phoenix Contact can custom-mark all UniCard markers according to your specifications

Commercial data

Item number	0829484
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG2
Product key	BG2118
Catalog page	Page 132 (C-3-2019)
GTIN	4046356571111
Weight per piece (including packing)	14.96 g
Weight per piece (excluding packing)	13.79 g
Customs tariff number	39269097
Country of origin	PL

0829484

https://www.phoenixcontact.com/in/products/0829484



Technical data

Notes

General	Can be labeled via thermal transfer
Product properties	
Product type	Terminal marking
Pitch	3.5 mm
Туре	high
Data management status	
Article revision	03
Marking	
Number of individual labels	102
Number of individual labels per row	17
Identification technology	Thermal transfer for sheets and cards
Dimensions	
Width	2.95 mm
Text field width	2.95 mm
Height	4.6 mm
Text field height	10.50 mm
Length	10.5 mm
Pitch	3.5 mm

Material specifications

Color	white
Material	PC
Flammability rating according to UL 94	V0
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	free from silicone and halogen

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish	
Result	Test passed
Test for substances that would hinder coating with paint or varnish	
Result	Test passed
Scratch test for the determining scratch resistance	
Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N



0829484

https://www.phoenixcontact.com/in/products/0829484

Result	Test passed
Tesafilm test	
Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed
result	
UV resistance	
Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h
Temperature resistance	
Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 100 °C (121 °C)	Test passed
Wipe resistance of inscriptions	
Specification	DIN EN 61010-1 (VDE 0411-01):2020-03
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
lsopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed
Testing in a condensation changing climate in the preser	nce of sulfur dioxide
Specification	ISO 22479:2019-05
Result	Test passed
Procedure	Method B
Cycles	2
Salt spray test	
Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h
Ambient conditions	
Ambient temperature (operation)	-40 °C 120 °C

0829484

https://www.phoenixcontact.com/in/products/0829484

Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years
andards and regulations Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-	DIN EN 61010-1 (VDE 0411-1)

PHŒNIX CONTACT



https://www.phoenixcontact.com/in/products/0829484



Classifications

ECLASS

ECLASS-11.0	27281101
ECLASS-12.0	27281101
ECLASS-13.0	27281101

ETIM

	ETIM 9.0	EC000761
U	NSPSC	
	UNSPSC 21.0	39131500

0829484

https://www.phoenixcontact.com/in/products/0829484



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

0829484

https://www.phoenixcontact.com/in/products/0829484



Accessories

THERMOMARK CARD 2.0 - Thermal transfer printer

1085267 https://www.phoenixcontact.com/in/products/1085267



Thermal transfer printer for card materials, including Euro/US power cable and USB cable. User manual printed in German and English. Magazine for UCT-TM.. . sheets and magazines for US-... cards. One packing unit each UCT-TM 6, US-EMLP (85,6x54), ink ribbon = 50 m

BLUEMARK ID - Printer

1003334 https://www.phoenixcontact.com/in/products/1003334



Monochrome printer with UV inkjet technology and integrated "MARKING system app" identification software. 7" touch color display for printing plastic labels in UC, UCT, US, and UM format, as well as metal labels.

0829484

https://www.phoenixcontact.com/in/products/0829484



BLUEMARK ID COLOR - Printer

1002329

https://www.phoenixcontact.com/in/products/1002329



CMYK multicolor printer with UV inkjet technology, with integrated "MARKING system app" identification software, 7" touch color display for printing plastic labels in UC, UCT, and UM format, as well as metal labels.

TOPMARK NEO - Laser marker

1012015 https://www.phoenixcontact.com/in/products/1012015



Laser marking system for the efficient marking of metal or plastic marking material from the LS..., UCT..., UC.../PP..., UM... product families.

0829484

https://www.phoenixcontact.com/in/products/0829484



THERMOMARK-RIBBON 110/50-TC - Ink ribbon

0801384

https://www.phoenixcontact.com/in/products/0801384



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 50 m, roll length: 50 m, width: 110 mm, color: black

THERMOMARK-RIBBON 110-TC - Ink ribbon

0801371 https://www.phoenixcontact.com/in/products/0801371



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 300 m, roll length: 300 m, width: 110 mm, color: black

0829484

https://www.phoenixcontact.com/in/products/0829484



TMP-RIBBON 110 BK 100 - Ink ribbon cartridge

0803374

https://www.phoenixcontact.com/in/products/0803374

Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups UCT. .., US..., and UM..., length: 70 m, roll length: 70 m, width: 110 mm, color: black



BM ID-CARTR. BK - Ink cartridge

1044345 https://www.phoenixcontact.com/in/products/1044345



Replacement UV fluid, 23 ml, color: black

0829484

https://www.phoenixcontact.com/in/products/0829484



BM ID-CARTR. CY - Ink cartridge

1044346

https://www.phoenixcontact.com/in/products/1044346



Replacement UV fluid, 23 ml, color: cyan

BM ID-CARTR. MA - Ink cartridge

1044347 https://www.phoenixcontact.com/in/products/1044347



Replacement UV fluid, 23 ml, color: magenta

0829484

https://www.phoenixcontact.com/in/products/0829484



BM ID-CARTR. YE - Ink cartridge

1044348

https://www.phoenixcontact.com/in/products/1044348



Replacement UV fluid, 23 ml, color: yellow

BLUEMARK CLED-FLUID-CARTR. - Ink cartridge

5146662 https://www.phoenixcontact.com/in/products/5146662

Cartridge, for replacement, 20 ml UV color, black, including cleaning cartridge



0829484

https://www.phoenixcontact.com/in/products/0829484



BLUEMARK FLUID-CARTRIDGE - Ink cartridge

5147421

https://www.phoenixcontact.com/in/products/5147421

Cartridge, for replacement, 28 ml UV color, black including cleaning cartridge



TMP-UCT-MAG1 - Magazine

0803342 https://www.phoenixcontact.com/in/products/0803342



Magazine, for the THERMOMARK PRIME and the THERMOMARK CARD, for accommodating UCT-TM..., UCT1(U)-TM..., UCT5-TM..., UCT-EM (5x10), UCT-EM (6x10), length: 0.166 m, width: 114 mm, height: 11.5 mm

0829484

https://www.phoenixcontact.com/in/products/0829484



BM ID-MAG20 - Magazine

1044356

https://www.phoenixcontact.com/in/products/1044356



Infeed magazine for accommodating a max. of 20 UniCard sheets

BM ID-MAG40 - Magazine

1044357 https://www.phoenixcontact.com/in/products/1044357



Infeed magazine for accommodating a maxi. of 40 UniCard sheets

0829484

https://www.phoenixcontact.com/in/products/0829484



TOPMARK LASER-MAG UCT-A - Magazine

0803141

https://www.phoenixcontact.com/in/products/0803141

Magazine for the TOPMARK LASER, for accommodating UCT material automatically



TOPMARK LASER-MAG UCT-M - Magazine

0803143 https://www.phoenixcontact.com/in/products/0803143

Magazine for the TOPMARK LASER, for accommodating UCT material manually



0829484

https://www.phoenixcontact.com/in/products/0829484

PHŒNIX CONTACT

THERMOMARK CARD - Thermal transfer printer

5146464

https://www.phoenixcontact.com/in/products/5146464

Thermal transfer printer for cards



THERMOMARK PRIME - Thermal transfer printer

5148888

https://www.phoenixcontact.com/in/products/5148888



Mobile thermal transfer printer for card materials, including power supply unit, Euro/US power cable, and USB cable. User manual printed in German and English. Magazine for UCT-TM... sheets and magazine for US-... cards. One packing unit each UCT-TM 6, US-EMLP (85,6x54), ink ribbon cartridge = 70 m

0829484

https://www.phoenixcontact.com/in/products/0829484



BLUEMARK CLED - Printer

5147999

https://www.phoenixcontact.com/in/products/5147999



Printers with LED-UV technology for printing plastic labels in UniCard format.

THERMOMARK CARD-UCT-MAG1 - Magazine

5146480

https://www.phoenixcontact.com/in/products/5146480



Magazine for the THERMOMARK CARD printer, for accommodating UCT sheets (UCT-TM..., UCT1-TM..., UCT5-TM...)

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in