

KMK HP (25X6) - Cable marker carrier



0830720

<https://www.phoenixcontact.com/in/products/0830720>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Cable marker carrier, transparent, unlabeled, mounting type: Assembly with cable ties, cable diameter: ≥ 6 mm, lettering field size: 25 x 6 mm



Your advantages

- Plastic cable markers for insert labels, for assembly with cable binders
- Plastic cable markers for marking and bundling conductors and cables indoors
- The markers have eyelets and are attached with cable binders
- The marked insert label is protected from dirt by the sealing cap

Commercial Data

Item number	0830720
Packing unit	100 pc
Minimum order quantity	100 pc
Sales Key	BG2
Product Key	BG231A
Catalog Page	Page 238 (C-3-2019)
GTIN	4046356725781
Weight per Piece (including packing)	1.5 g
Weight per Piece (excluding packing)	1.4 g
Customs tariff number	39269097
Country of origin	DE

KMK HP (25X6) - Cable marker carrier



0830720

<https://www.phoenixcontact.com/in/products/0830720>

Technical Data

Product properties

Product type	Marker carrier cable
Type	Mounting set

Dimensions

Width	6 mm
Height	25 mm
Length	25 mm

External dimensions

Outside diameter	6 mm ... 50 mm
------------------	----------------

Material specifications

Color	transparent
Material	PC
Flammability rating according to UL 94	V0
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	halogen-free

Cable/line

External cable diameter	≥ 6 mm
-------------------------	--------

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03
Result	Test passed
Test duration	96 h

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 125 °C (150 °C)	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed

KMK HP (25X6) - Cable marker carrier



0830720

<https://www.phoenixcontact.com/in/products/0830720>

Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

High pressure test

Specification	IEC 60529:2001-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
Ambient temperature (assembly)	-40 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	2 years

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	Assembly with cable ties
---------------	--------------------------

KMK HP (25X6) - Cable marker carrier



0830720

<https://www.phoenixcontact.com/in/products/0830720>

Classifications

ECLASS

ECLASS-11.0	27281105
ECLASS-12.0	27281105
ECLASS-13.0	27281105

ETIM

ETIM 8.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

KMK HP (25X6) - Cable marker carrier



0830720

<https://www.phoenixcontact.com/in/products/0830720>

Accessories

UCT-EMP (25X6) - Snap-in markers

1014117

<https://www.phoenixcontact.com/in/products/1014117>



Snap-in markers, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, lettering field size: 25 x 6 mm, Number of individual labels: 15

ESL (25X6) - Insert strip

0801849

<https://www.phoenixcontact.com/in/products/0801849>



Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems: Laser printer, mounting type: insert, lettering field size: 25 x 6 mm, Number of individual labels: 252

KMK HP (25X6) - Cable marker carrier

0830720

<https://www.phoenixcontact.com/in/products/0830720>



US-EMP (25X6)-1 - Snap-in markers

0802754

<https://www.phoenixcontact.com/in/products/0802754>



Snap-in markers, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, lettering field size: 25 x 6 mm, Number of individual labels: 84

EMT (25X6)R - Insert label

0817264

<https://www.phoenixcontact.com/in/products/0817264>



Insert label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: insert, cable diameter range: 10 ... 25 mm, lettering field size: 25 x 6 mm, Number of individual labels: 5000

KMK HP (25X6) - Cable marker carrier

0830720

<https://www.phoenixcontact.com/in/products/0830720>



MM-EMT (EX6)R C1 WH/BK - Insert label

0803963

<https://www.phoenixcontact.com/in/products/0803963>



Insert label, Roll, white/black, unlabeled, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: snapped, lettering field size: continuous x 4 mm

WT-HP HF 3,6X140 - Cable tie

0830982

<https://www.phoenixcontact.com/in/products/0830982>



Cable binders for quick and secure bundling, standard version

KMK HP (25X6) - Cable marker carrier

0830720

<https://www.phoenixcontact.com/in/products/0830720>

WT-HP HF 4,8X200 - Cable tie

0830983

<https://www.phoenixcontact.com/in/products/0830983>



Cable binders for quick and secure bundling, standard version

WT-HP HF 4,5X290 - Cable tie

0830984

<https://www.phoenixcontact.com/in/products/0830984>



Cable binders for quick and secure bundling, standard version

KMK HP (25X6) - Cable marker carrier

0830720

<https://www.phoenixcontact.com/in/products/0830720>



WT-HT HF 3,6X140 - Cable tie

3240782

<https://www.phoenixcontact.com/in/products/3240782>



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

WT-HT HF 3,6X200 - Cable tie

3240784

<https://www.phoenixcontact.com/in/products/3240784>



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

KMK HP (25X6) - Cable marker carrier

0830720

<https://www.phoenixcontact.com/in/products/0830720>



WT-HT HF 4,5X200 - Cable tie

3240786

<https://www.phoenixcontact.com/in/products/3240786>



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

WT-HT HF 4,5X290 - Cable tie

3240788

<https://www.phoenixcontact.com/in/products/3240788>



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

KMK HP (25X6) - Cable marker carrier

0830720

<https://www.phoenixcontact.com/in/products/0830720>



WT-HT HF 3,6X140 BK - Cable tie

3240783

<https://www.phoenixcontact.com/in/products/3240783>



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

WT-HT HF 3,6X200 BK - Cable tie

3240785

<https://www.phoenixcontact.com/in/products/3240785>



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

KMK HP (25X6) - Cable marker carrier



0830720

<https://www.phoenixcontact.com/in/products/0830720>

WT-HT HF 4,5X200 BK - Cable tie

3240787

<https://www.phoenixcontact.com/in/products/3240787>



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

WT-HT HF 4,5X290 BK - Cable tie

3240789

<https://www.phoenixcontact.com/in/products/3240789>



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in