

KMK 3 - Plastic cable markers

1005211

<https://www.phoenixcontact.com/in/products/1005211>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plastic cable markers, transparent, unlabeled, mounting type: Assembly with cable ties, cable diameter range: 16 ... 35 mm, lettering field size: 40 x 17 mm

Your advantages

- Plastic cable markers for marking and bundling conductors and cables indoors
- Labeling service: Phoenix Contact can custom-label all insert labels for plastic cable markers according to your requirements
- The marked insert label is protected from dirt by the sealing cap

Commercial Data

Item number	1005211
Packing unit	50 pc
Minimum order quantity	50 pc
Sales Key	BG2
Product Key	BG231A
Catalog Page	Page 237 (C-3-2019)
GTIN	4017918012441
Weight per Piece (including packing)	5.598 g
Weight per Piece (excluding packing)	5.5 g
Customs tariff number	39269097
Country of origin	DE

KMK 3 - Plastic cable markers



1005211

<https://www.phoenixcontact.com/in/products/1005211>

Technical Data

Product properties

Product type	Marker carrier cable
Type	Mounting set

Dimensions

Width	17 mm
Height	17 mm
Length	40 mm

External dimensions

Outside diameter	16 mm ... 35 mm
------------------	-----------------

Material specifications

Color	transparent
Material	Polyethylene
Components	free from silicone and halogen

Cable/line

External cable diameter	16 mm ... 35 mm
-------------------------	-----------------

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h
Specification	ISO 175:2010 (following)
Test duration	168 h

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

KMK 3 - Plastic cable markers



1005211

<https://www.phoenixcontact.com/in/products/1005211>

Ambient temperature (operation)	-40 °C ... 80 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	2 years

Mounting

Mounting type	Assembly with cable ties
---------------	--------------------------

KMK 3 - Plastic cable markers



1005211

<https://www.phoenixcontact.com/in/products/1005211>

Classifications

ECLASS

ECLASS-11.0	27281105
ECLASS-12.0	27281105
ECLASS-13.0	27281105

ETIM

ETIM 8.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

KMK 3 - Plastic cable markers

1005211

<https://www.phoenixcontact.com/in/products/1005211>

Accessories

ESL 40X17 - Insert strip

0808095

<https://www.phoenixcontact.com/in/products/0808095>

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, perforated, mounting type: insert, lettering field size: 40 x 17 mm, Number of individual labels: 56



ES/KMK 3 - Insert strip

1005224

<https://www.phoenixcontact.com/in/products/1005224>

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, CMS-P1-PLOTTER, perforated, mounting type: insert, lettering field size: 40 x 17 mm, Number of individual labels: 10



KMK 3 - Plastic cable markers

1005211

<https://www.phoenixcontact.com/in/products/1005211>



ES/KMK 3-GB - Insert strip

1005088

<https://www.phoenixcontact.com/in/products/1005088>

Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, CMS-P1-PLOTTER, mounting type: insert, lettering field size: 17.2 x 39.75 mm, Number of individual labels: 52



US-EMP (40X17) - Snap-in markers

0829437

<https://www.phoenixcontact.com/in/products/0829437>

Snap-in markers, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, lettering field size: 40 x 17 mm, Number of individual labels: 16



KMK 3 - Plastic cable markers

1005211

<https://www.phoenixcontact.com/in/products/1005211>

EMT (40X17)R - Insert label

0817293

<https://www.phoenixcontact.com/in/products/0817293>



Insert label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: insert, cable diameter range: 16 ... 35 mm, lettering field size: 40 x 17 mm, Number of individual labels: 2300

EMT (EX17)R - Insert label

0804546

<https://www.phoenixcontact.com/in/products/0804546>



Insert label, for marking Siemens SIVACON label holder system, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: insert, lettering field size: 17 x 30000 mm

KMK 3 - Plastic cable markers



1005211

<https://www.phoenixcontact.com/in/products/1005211>

MM-EMT (EX17)R C1 WH/BK - Insert label

0803967

<https://www.phoenixcontact.com/in/products/0803967>



Insert label, Roll, white/black, unlabeled, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: snapped, lettering field size: continuous x 15 mm

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in