

1412776

https://www.phoenixcontact.com/in/products/1412776

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sleeve housing B24, for double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x Pg21, height: 60 mm, cable gland: none, Standard

Your advantages

• Good shielding in the event of electromagnetic interference

Commercial Data

Item number	1412776
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF7
Product Key	BF7APB
Catalog Page	Page 638 (C-2-2019)
GTIN	4055626060422
Weight per Piece (including packing)	242.3 g
Weight per Piece (excluding packing)	240.3 g
Customs tariff number	85389099
Country of origin	PL



1412776

https://www.phoenixcontact.com/in/products/1412776

Technical Data

Notes

General	for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
---------	--

Product properties

Туре	B24
Product type	Housing with locking latch
Application	Standard
No. of cable outlets	1
Type of the screw connection	1x Pg21
Housing type	Sleeve housing
Locking type	for double locking latch
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	S 1 120 - 44 -
Width	44 mm
Height	60 mm
Length	120 mm

Material specifications

Color	gray aluminum
Housing surface material	uncoated
Impact strength	IK09
Housing material	Die-cast aluminum, salt water resistant

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg21
Locking type	Pin

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
	4 (UL 50e)
	4X (UL 50e)



1412776

https://www.phoenixcontact.com/in/products/1412776

	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C 125 °C




https://www.phoenixcontact.com/in/products/1412776



Drawings

Dimensional drawing





Dimensional drawing



1412776

https://www.phoenixcontact.com/in/products/1412776

Approvals



cUL RecognizedApproval ID: E255026



UL RecognizedApproval ID: E255026



EAC

Approval ID: RU C-DE.Al30.B.01102



EAC

Approval ID: RU C-DE.BL08.B.00511



1412776

https://www.phoenixcontact.com/in/products/1412776

Classifications

UNSPSC 21.0

ECLASS

27440202
27440202
27440202
EC000437

31261500



1412776

https://www.phoenixcontact.com/in/products/1412776

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



1412776

https://www.phoenixcontact.com/in/products/1412776

Accessories

G-INS-PG21-M68N-NNES-S - Cable gland

1411175

https://www.phoenixcontact.com/in/products/1411175



Cable gland, material for screw connection: Nickel-plated brass, external cable diameter 13 mm ... 18 mm, shielding: no, connecting thread: Pg21, color: silver, with O-ring

G-INSEC-PG21-M68N-NNES-S - Cable gland

1411200

https://www.phoenixcontact.com/in/products/1411200



Cable gland, material for screw connection: Nickel-plated brass, external cable diameter 13 mm ... 18 mm, shielding: yes, connecting thread: Pg21, color: silver, with O-ring




1412776

https://www.phoenixcontact.com/in/products/1412776

US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/in/products/0830085





HC-B24-HCWD-PLR-BK - Protective cover

1346552

https://www.phoenixcontact.com/in/products/1346552



Protective cover B24, with double locking latch, protective cover material: PC, height: 25.4 mm, seal: yes



1412776

https://www.phoenixcontact.com/in/products/1412776

US-EMLP-HA (20X9) - Plastic label

0830989

https://www.phoenixcontact.com/in/products/0830989



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

WP-G HF IP66 PG21 BK - Screw connection

3240892

https://www.phoenixcontact.com/in/products/3240892



Cable gland, Pg thread, IP66 protection, straight



1412776

https://www.phoenixcontact.com/in/products/1412776

WP-G HF IP69K PG21 BK - Screw connection

3240878

https://www.phoenixcontact.com/in/products/3240878



Cable gland, Pg thread, IP68/69k protection, straight

WP-GA HF IP66 PG21 BK - Screw connection

3240920

https://www.phoenixcontact.com/in/products/3240920

Cable gland, Pg thread, IP66 protection, angled





1412776

https://www.phoenixcontact.com/in/products/1412776

WP-GA HF IP69K PG21 BK - Screw connection

3240906

https://www.phoenixcontact.com/in/products/3240906

Cable gland, Pg thread, IP68/69k protection, angled



WP-GR HF IP66 PG21 BK - Screw connection

3240948

https://www.phoenixcontact.com/in/products/3240948

Cable gland, Pg thread, IP66 protection, with strain relief





1412776

https://www.phoenixcontact.com/in/products/1412776

WP-GR HF IP69K PG21 BK - Screw connection

3240934

https://www.phoenixcontact.com/in/products/3240934



Cable gland, Pg thread, IP68/69k protection, with strain relief

WP-G PP HF PG21 - Screw connection

3240992

https://www.phoenixcontact.com/in/products/3240992

Cable gland made from PP with Pg thread, IP65 protection



1412776

https://www.phoenixcontact.com/in/products/1412776

WP-GT PP HF PG21 - Screw connection

3241006

https://www.phoenixcontact.com/in/products/3241006



Cable gland made from PP with Pg thread, rotatable, IP54 protection

WP-G BRASS IP40 PG21 - Screw connection

3241041

https://www.phoenixcontact.com/in/products/3241041



Cable gland made from brass with Pg thread, IP40 protection



1412776

https://www.phoenixcontact.com/in/products/1412776

WP-GT BRASS PG21 - Screw connection

3241027

https://www.phoenixcontact.com/in/products/3241027



Cable gland made from brass with Pg thread, rotatable, IP40 protection

WP-G BRASS IP65 PG21 - Screw connection

3241055

https://www.phoenixcontact.com/in/products/3241055



Cable gland made from brass with Pg thread, IP65 protection

Phoenix Contact 2023 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in