

# ATP-DIK 1,5 - Partition plate



1413272

<https://www.phoenixcontact.com/in/products/1413272>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Partition plate, length: 65.3 mm, width: 2 mm, height: 60 mm, color: gray



## Commercial Data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1413272             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales Key                            | BE1                 |
| Product Key                          | BE1Z1X              |
| Catalog Page                         | Page 480 (C-1-2019) |
| GTIN                                 | 4017918021238       |
| Weight per Piece (including packing) | 6.47 g              |
| Weight per Piece (excluding packing) | 6.46 g              |
| Customs tariff number                | 39269097            |
| Country of origin                    | DE                  |

# ATP-DIK 1,5 - Partition plate



1413272

<https://www.phoenixcontact.com/in/products/1413272>

## Technical Data

### Product properties

|              |                 |
|--------------|-----------------|
| Product type | Partition plate |
|--------------|-----------------|

### Dimensions

|        |         |
|--------|---------|
| Width  | 2 mm    |
| Height | 60 mm   |
| Length | 65.3 mm |

### Material specifications

|  |      |
|--|------|
| Color                                  | gray |
| Material                               | PA   |
| Flammability rating according to UL 94 | V2   |

### Environmental and real-life conditions

#### Ambient conditions

|  |   |
|--|---|
| Ambient temperature (operation)          | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)       |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C   |
| Ambient temperature (actuation)          | -5 °C ... 70 °C   |
| Permissible humidity (storage/transport) | 30 % ... 70 %   |

# ATP-DIK 1,5 - Partition plate



1413272

<https://www.phoenixcontact.com/in/products/1413272>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141133 |
| ECLASS-12.0 | 27141133 |
| ECLASS-13.0 | 27250301 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC000886 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# ATP-DIK 1,5 - Partition plate

1413272

<https://www.phoenixcontact.com/in/products/1413272>



## Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.  
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420  
[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)