


VS-OE-OE-93A-100,0 - Data cable



1416392

<https://www.phoenixcontact.com/in/products/1416392>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Data cable, PROFINET CAT5 (100 Mbps), 4-position, PVC, green-yellow RAL 6018, shielded, free cable end, on free cable end, cable length: 100 m

Commercial data

Item number	1416392
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF1
Product key	BF1LFA
Catalog page	Page 392 (C-2-2019)
GTIN	4046356474313
Weight per piece (including packing)	6,094 g
Weight per piece (excluding packing)	6,094 g
Customs tariff number	85444290
Country of origin	DE

1416392

<https://www.phoenixcontact.com/in/products/1416392>

Technical data

Notes

General	This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 9.1.1 Balanced Cables (Type A,B,C)
---------	---

Product properties

Product type	Data cable by the meter
Application	Standard
Sensor type	PROFINET
Number of positions	4
Shielded	yes

Electrical properties

Transmission medium	Copper
Transmission characteristics (category)	CAT5 (IEC 11801:2002)

Interfaces

Signal type/category	PROFINET CAT5 (IEC 11801), 100 Mbps
----------------------	-------------------------------------

Connector

Connection 1

Type	free cable end
------	----------------


Connection 2

Type	free cable end
------	----------------

Cable/line

Cable length	100 m
--------------	-------

PROFINET [93A]

Dimensional drawing	
UL AWM Style	2464 (80°C/300 V)
Number of positions	4
Shielded	yes
Cable type	PROFINET [93A]

VS-OE-OE-93A-100,0 - Data cable



1416392

<https://www.phoenixcontact.com/in/products/1416392>

Conductor structure	1x4xAWG22/1, SF/TQ
Signal runtime	5.3 ns/m
Signal speed	0.68 c
Conductor structure signal line	1x 0.65 mm
AWG signal line	22
Conductor cross section	4x 0.34 mm ²
Wire diameter incl. insulation	1.5 mm ±0.05 mm
External cable diameter	6.50 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	green-yellow RAL 6018
Conductor material	Tin-plated Cu wire
Material wire insulation	PE
Single wire, color	white, yellow, blue, orange
Overall twist	Star quad
Optical shield covering	90 %
Max. conductor resistance	≤ 57.1 Ω/km
Coupling resistance	< 10.00 mΩ/m (at 10 MHz)
Wave impedance	100 Ω ±15 Ω (at 1 ... 100 MHz)
Nominal voltage, cable	300 V
Test voltage Core/Core	2500 V DC
Test voltage Core/Shield	2500.00 V DC
Flame resistance	According to VW-1
Resistance to oil	according to IEC 60811-2-1
Ambient temperature (operation)	-25 °C ... 80 °C
Ambient temperature (installation)	-5 °C ... 50 °C

VS-OE-OE-93A-100,0 - Data cable



1416392

<https://www.phoenixcontact.com/in/products/1416392>

Classifications

ECLASS

ECLASS-11.0	27061801
ECLASS-12.0	27061801
ECLASS-13.0	27061801

ETIM

ETIM 9.0	EC003249
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

VS-OE-OE-93A-100,0 - Data cable



1416392

<https://www.phoenixcontact.com/in/products/1416392>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

VS-OE-OE-93A-100,0 - Data cable

1416392

<https://www.phoenixcontact.com/in/products/1416392>



Accessories

VS-CABLE-STRIP-VARIO - Stripping tool

1657407

<https://www.phoenixcontact.com/in/products/1657407>

Stripping tool, for the multi-level stripping of shielded cables



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in