

https://www.phoenixcontact.com/in/products/2748577



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 8-pos.



Your advantages

- · In combination with other devices in the distribution board, such as residual current devices and miniature circuit breakers
- · Practical wiring of all common applications
- · For combinations of lightning and surge arresters

Commercial Data

Item number	2748577
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CL1
Product Key	CL132Z
Catalog Page	Page 101 (C-4-2019)
GTIN	4017918062545
Weight per Piece (including packing)	38.7 g
Weight per Piece (excluding packing)	38.7 g
Customs tariff number	85369095
Country of origin	DE



https://www.phoenixcontact.com/in/products/2748577



Technical Data

Product properties

Туре	Comb bridge
Product type	Bridge
Number of positions	8
ectrical properties	

Ele

Number of phases	1
Nominal current I _N	100 A

Dimensions

Height	144.4 mm
--------	----------

Material specifications

Color	gray
Contact material	E-Cu 58
Housing material	Plastic



https://www.phoenixcontact.com/in/products/2748577



Classifications

ECLASS

	ECLASS-11.0	27371306
	ECLASS-12.0	27371306
	ECLASS-13.0	27371306
ΕT	ТІМ	
	ETIM 8.0	EC000215

UNSPSC

UNSPSC 21.0	39121600
-------------	----------



https://www.phoenixcontact.com/in/products/2748577



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



https://www.phoenixcontact.com/in/products/2748577



Accessories

CUTFOX-FBS - Front cutter

1212124

https://www.phoenixcontact.com/in/products/1212124



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges

CUTFOX 25 VDE - Cable-cutting tool

1212127

https://www.phoenixcontact.com/in/products/1212127



Cable cutter, precision blade with macro-notching, for copper and aluminum up to 70 mm 2 , VDE 1000 V AC/ 1500 V DC tested

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in