

RAD-CAB-EF393- 3M - Antenna cable



2867649

<https://www.phoenixcontact.com/in/products/2867649>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Antenna cable, outside diameter: 10 mm (0.4 in.), inner conductor: stranded, attenuation: 1.0 / 1.8 / 3.1 dB at 0.9 / 2.4 / 5.8 GHz, connection: 2 x N (male), cable length: 3 m (10 ft.)



Your advantages

- Halogen-free
- Easy installation, thanks to flexible inner conductor
- Flame-retardant
- UV resistant
- Oil-resistant
- For outdoor installation

Commercial Data

Item number	2867649
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	DNN
Product Key	DNN2Z1
Catalog Page	Page 391 (C-6-2019)
GTIN	4017918939014
Weight per Piece (including packing)	600 g
Weight per Piece (excluding packing)	590 g
Customs tariff number	85442000
Country of origin	PL

Technical Data

Product properties

Product type	Coaxial cable
--------------	---------------

Electrical properties

Frequency range	0.3 GHz ... 6 GHz
Impedance	50 Ω

Connection data

Connector connection

Connection method	N (male)
Notes	Both sides
Connection method	N (male)

Material specifications

Outer sheath, material	RADOX®(LSFH)
------------------------	--------------

Cable/line

Cable length	3 m
Cable type	EF 393
External cable diameter	10.00 mm
Outer sheath, material	RADOX®(LSFH)
External sheath, color	black
Bending radius, long-term	50.00 mm
868 / 900 MHz	~ 1 dB (Attenuation of entire cable)
2.4 GHz	~ 1.8 dB (Attenuation of entire cable)
5.8 GHz	~ 3.1 dB (Attenuation of entire cable)
Resistance to oil	very good oil and chemical resistance

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C
Ambient temperature (storage/transport)	-40 °C ... 105 °C
Ambient temperature (assembly)	-20 °C ... 60 °C
Resistance to oil	very good oil and chemical resistance

Approvals

CE

Certificate	CE-compliant
-------------	--------------

Standards and regulations

Resistance to oil	very good oil and chemical resistance
-------------------	---------------------------------------

RAD-CAB-EF393- 3M - Antenna cable



2867649

<https://www.phoenixcontact.com/in/products/2867649>

Standards/specifications	DIN EN 60332-1-2
	UL 1581
Standards/specifications	IEC 60754
Standards/specifications	IEC 60068-2-5

Mounting

Assembly instructions	Outdoors and indoors
-----------------------	----------------------

RAD-CAB-EF393- 3M - Antenna cable



2867649

<https://www.phoenixcontact.com/in/products/2867649>

Approvals



EAC

Approval ID: 19060508

RAD-CAB-EF393- 3M - Antenna cable



2867649

<https://www.phoenixcontact.com/in/products/2867649>

Classifications

ECLASS

ECLASS-11.0	27060310
ECLASS-12.0	27060310
ECLASS-13.0	27060310

ETIM

ETIM 8.0	EC001682
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

RAD-CAB-EF393- 3M - Antenna cable



2867649

<https://www.phoenixcontact.com/in/products/2867649>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25; For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in