

FL SFP LX - Media module



2891767

<https://www.phoenixcontact.com/in/products/2891767>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Gigabit SFP module for transmission up to 30 km with a wavelength of 1310 nm.



Product Description

SFP module with a data transmission speed of 1000 Mbps, a wavelength of 1310 nm, and a maximum transmission length of 30 km.

Your advantages

- MSA compliant

Commercial Data

Item number	2891767
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	DNN
Product Key	DNN1ZS
Catalog Page	Page 333 (C-6-2019)
GTIN	4046356166775
Weight per Piece (including packing)	30.6 g
Weight per Piece (excluding packing)	30.6 g
Customs tariff number	85176200
Country of origin	TW

FL SFP LX - Media module



2891767

<https://www.phoenixcontact.com/in/products/2891767>

Technical Data

Dimensions

Width	13.7 mm
Height	8.95 mm
Length	56.5 mm

Material specifications

Housing material	Metal
------------------	-------

Mounting

Mounting type	Insert in SFP slot
Connection method	To insert in SFP slot

Interfaces

Ethernet FO

Connection method	LC
Transmission speed	1 Gbps
Transmit capacity, minimum	-5 dBm
Transmit capacity, maximum	0 dBm
Minimum receiver sensitivity	-24 dBm
Maximum receiver sensitivity	-3 dBm
Transmission physics	Single-mode fiberglass
Transmission length	30 km (Fiberglass 9/125) 250 m (Fiberglass 62.5/125)
Wavelength	1310 nm
Signal LEDs	depending on the Factoryline device
No. of channels	1 (LC single mode)
Transmit capacity, minimum	-5 dBm
Transmit capacity, maximum	0 dBm
Minimum receiver sensitivity	-3 dBm
Maximum receiver sensitivity	-24 dBm

Product properties

Type	Factoryline devices with SFP slot
Product type	SFP module
MTTF	748 Years (Telcordia SR-332, temperature factor at 40°C = 1, stress factor at 50% = 1, environmental factor = 1)
Format	SFP (Small Form-factor Pluggable)

Signaling

Status display	via a Factoryline device
----------------	--------------------------

Electrical properties

FL SFP LX - Media module



2891767

<https://www.phoenixcontact.com/in/products/2891767>

Maximum power dissipation for nominal condition	1 W
Transmission medium	FO

Supply

Supply voltage	3.3 V (via Factoryline switch)
Power supply connection	via SFP slot
Max. current consumption	300 mA
Current consumption	300 mA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C (non-condensing)
Ambient temperature (storage/transport)	-40 °C ... 85 °C (non-condensing)
Permissible humidity (operation)	30 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	30 % ... 95 % (non-condensing)
Vibration (operation)	in acc. with IEC 60068-2-6: 5g, 150 Hz
Air pressure (operation)	86 kPa ... 108 kPa (1500 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)

FL SFP LX - Media module



2891767

<https://www.phoenixcontact.com/in/products/2891767>

Approvals



cUL Recognized

Approval ID: FILE E 140403



UL Recognized

Approval ID: FILE E 140403



EAC

Approval ID: RU*DE*08.B.00731/19



DNV GL

Approval ID: TAA00000YV



LR

Approval ID: LR22250919TA



NK

Approval ID: TA19464M



BV

Approval ID: 48146/A1 BV



RINA

Approval ID: ELE162721XG

FL SFP LX - Media module



2891767

<https://www.phoenixcontact.com/in/products/2891767>

Classifications

ECLASS

ECLASS-11.0	19179090
ECLASS-12.0	19179090
ECLASS-13.0	19179090

ETIM

ETIM 8.0	EC000310
----------	----------

UNSPSC

UNSPSC 21.0	43222600
-------------	----------

FL SFP LX - Media module

2891767

<https://www.phoenixcontact.com/in/products/2891767>



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

FL SFP LX - Media module

2891767

<https://www.phoenixcontact.com/in/products/2891767>



Accessories

FOC-LC:PA-ST:PA-OS2:D01/1 - FO patch cable

1115596

<https://www.phoenixcontact.com/in/products/1115596>

Single-mode OS2 duplex jumper, LC-ST, UPC polishing, length 1 m



FOC-LC:PA-ST:PA-OS2:D01/2 - FO patch cable

1115595

<https://www.phoenixcontact.com/in/products/1115595>

Single-mode OS2 duplex jumper, LC-ST, UPC polishing, length 2 m



FL SFP LX - Media module

2891767

<https://www.phoenixcontact.com/in/products/2891767>




FOC-LC:PA-LC:PA-OS2:D01/1 - FO patch cable

1115636

<https://www.phoenixcontact.com/in/products/1115636>

Single-mode OS2 duplex jumper, LC-LC, UPC polishing, length 1 m




FOC-LC:PA-LC:PA-OS2:D01/2 - FO patch cable

1115629

<https://www.phoenixcontact.com/in/products/1115629>

Single-mode OS2 duplex jumper, LC-LC, UPC polishing, length 2 m



FL SFP LX - Media module

2891767

<https://www.phoenixcontact.com/in/products/2891767>




FOC-LC:PA-SC:PA-OS2:D01/1 - FO patch cable

1115618

<https://www.phoenixcontact.com/in/products/1115618>

Single-mode OS2 duplex jumper, LC-SC, UPC polishing, length 1 m




FOC-LC:PA-SC:PA-OS2:D01/2 - FO patch cable

1115617

<https://www.phoenixcontact.com/in/products/1115617>

Single-mode OS2 duplex jumper, LC-SC, UPC polishing, length 2 m



Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in