

2959683

https://www.phoenixcontact.com/za/products/2959683

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Side element with foot, 5 mm wide (right), for mounting on NS 32 or NS 35/7.5. PCB width: 107.5 mm



Your advantages

- · Easy installation
- · Flexible size and shape
- · Inexpensive as a result of reducing the number of separate housing parts

Commercial Data

| Item number | 2959683 |
|--------------------------------------|---------------------|
| Packing unit | 10 pc |
| Minimum order quantity | 1 pc |
| Sales Key | 101 |
| Product Key | ACHDBA |
| Catalog Page | Page 757 (C-1-2013) |
| GTIN | 4017918086336 |
| Weight per Piece (including packing) | 9,06 g |
| Weight per Piece (excluding packing) | 8,98 g |
| Customs tariff number | 85389099 |
| Country of origin | PL |



https://www.phoenixcontact.com/za/products/2959683



Technical Data

Product properties

| Product type | Panel mounting base side part |
|------------------------------|-------------------------------|
| Product family | UM108 |
| Туре | Lateral element (right) |
| Housing type | Press-drawn section housings |
| Ventilation openings present | no |
| Housing series | UM |

Dimensions

| Width | 5 mm |
|--------|----------|
| Height | 125.4 mm |
| Depth | 37.6 mm |

Material specifications

| Color | green (6021) |
|--|--------------|
| Flammability rating according to UL 94 | V0 |
| Surface characteristics | untreated |
| Housing material | Polyamide |

Environmental and real-life conditions

Ambient conditions

| Ambient temperature (operation) | -40 °C 105 °C (depending on power dissipation) |
|---|--|
| Ambient temperature (storage/transport) | -40 °C 55 °C |
| Ambient temperature (assembly) | -5 °C 100 °C |
| Relative humidity (storage/transport) | 80 % |

Mounting

| Mounting type | DIN rail mounting |
|---------------|-------------------|

Packaging specifications

| Type of packaging | packed in cardboard |
|----------------------|---------------------|
| Outer packaging type | Carton |



2959683

https://www.phoenixcontact.com/za/products/2959683

Approvals



EAC

Approval ID: B.01687



UL RecognizedApproval ID: FILE E 240868



2959683

https://www.phoenixcontact.com/za/products/2959683

Classifications

| | ECLASS-11.0 | 27182701 |
|----------------|-------------|----------|
| E ⁻ | ГІМ | |
| | ETIM 8.0 | EC002779 |
| UNSPSC | | |
| | UNSPSC 21.0 | 31261500 |



https://www.phoenixcontact.com/za/products/2959683



Environmental Product Compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (Pty) Ltd. 36 Lyn Road P.O. Box 916 ZA-Ferndale 2160

+27/11/801-8200 info@phoenixcontact.co.za