3001596

https://www.phoenixcontact.com/in/products/3001596



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red

### **Commercial Data**

| Item number                          | 3001596            |
|--------------------------------------|--------------------|
| Packing unit                         | 50 рс              |
| Minimum order quantity               | 50 pc              |
| Sales Key                            | BE2                |
| Product Key                          | BE2Z2X             |
| Catalog Page                         | Page 98 (C-1-2019) |
| GTIN                                 | 4046356891189      |
| Weight per Piece (including packing) | 3 g                |
| Weight per Piece (excluding packing) | 2.9 g              |
| Customs tariff number                | 85366990           |
| Country of origin                    | CN                 |

3001596

https://www.phoenixcontact.com/in/products/3001596




## **Technical Data**

### Product properties

| Product type                           | Jumper   |
|--|--|
| Number of positions                    | 5  |
| Pitch                                  | 6.2 mm   |
| Electrical properties                  |  |
| Maximum load current                   | 24 A (The current values for the jumpers can deviate when used<br>in different modular terminal blocks. The precise values can be<br>found in the accessories data for the respective modular terminal<br>blocks.) |
| Connection data                        |  |
| Maximum load current                   | 24 A (The current values for the jumpers can deviate when used<br>in different modular terminal blocks. The precise values can be<br>found in the accessories data for the respective modular terminal<br>blocks.) |
| Dimensions                             |  |
| Pitch                                  | 6.2 mm   |
| Material specifications                |  |
| Color                                  | red  |
| Material                               | Copper   |
| Flammability rating according to UL 94 | VO   |
| Insulating material                    | PA   |
| Mounting                               |  |
| Mounting type                          | Plug-in mounting   |
|  |  |

3001596 https://www.phoenixcontact.com/in/products/3001596

## Drawings



Schematic diagram





3001596

https://www.phoenixcontact.com/in/products/3001596



## Classifications

### ECLASS

| ECLASS-11.0 | 27141140 |
|-------------|----------|
| ECLASS-12.0 | 27141140 |
| ECLASS-13.0 | 27250303 |

### ETIM

|        | ETIM 8.0    | EC000489 |  |
|--------|-------------|----------|--|
| UNSPSC |             |          |  |
|        | UNSPSC 21.0 | 39121400 |  |



3001596 https://www.phoenixcontact.com/in/products/3001596



## **Environmental Product Compliance**

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

3001596 https://www.phoenixcontact.com/in/products/3001596



Accessories

CUTFOX-FBS - Front cutter

1212124 https://www.phoenixcontact.com/in/products/1212124



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges

#### FBSC - Protective cap

3012325 https://www.phoenixcontact.com/in/products/3012325



Covering hood, provides reliable shock protection when using cut-to-length FBS . ...-5 and FBS ...-6 bridges, color: red

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in