3034468

https://www.phoenixcontact.com/in/products/3034468

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Switching jumper, pitch: 8.2 mm, number of positions: 2, length: 25 mm, color: gray/orange

Commercial data

Item number	3034468
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE2
Product key	BE2Z2X
Catalog page	Page 116 (C-1-2019)
GTIN	4046356281065
Weight per piece (including packing)	11.61 g
Weight per piece (excluding packing)	11.5 g
Customs tariff number	85366990
Country of origin	PL

3034468

https://www.phoenixcontact.com/in/products/3034468



Technical data

Product properties

Product type	Switching jumper
Number of positions	2
Pitch	8.2 mm
Potentials	1
Data management status	
Article revision	02
ectrical properties	
Maximum load current	30 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
onnection data	
Maximum load current	30 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be

Dimensions

Width	16.4 mm
Height	24.7 mm
Depth	47.42 mm
Length	24.7 mm
Pitch	8.2 mm

blocks.)

found in the accessories data for the respective modular terminal

Material specifications

Color	multicolored
	gray (RAL 7042)
	orange (RAL 2003)
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

3034468

https://www.phoenixcontact.com/in/products/3034468



Mounting

Mounting type

Plug-in mounting

3034468

https://www.phoenixcontact.com/in/products/3034468



Classifications

ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27250303

ETIM

	ETIM 9.0	EC000489
UNSPSC		
	UNSPSC 21.0	39121400

3034468

https://www.phoenixcontact.com/in/products/3034468



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	
EF3.0 Climate Change		
CO2e kg	0.078 kg CO2e	

3034468 https://www.phoenixcontact.com/in/products/3034468



Accessories

SL-SB - Switching lock

3035761 https://www.phoenixcontact.com/in/products/3035761



Switching lock, for additional locking of short-circuit switching elements in current transformer measuring circuits, depth: 13.6 mm, width: 12.5 mm, height: 16.3 mm, color: white

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in