

https://www.phoenixcontact.com/in/products/3063167



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Small, slotted cable sleeves suitable for conductors with a diameter of 8-9 mm.

Product description

Slotted sleeves for accommodating preassembled cables and lines of 8 mm ... 9 mm diameter, can be used in the KEL sealing frames: KEL 16/4, KEL 16/8, KEL 24/4, KEL 24/5, KEL 24/7, KEL 24/10. When mounted, the sleeves simultaneously function as strain relief according to DIN EN 50262.

Commercial data

Item number	3063167
Packing unit	1 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	BF7
Product key	BF7CCX
Catalog page	Page 686 (CL-2009)
GTIN	4046356300940
Weight per piece (including packing)	8.19 g
Weight per piece (excluding packing)	7.86 g
Customs tariff number	40169300
Country of origin	DE



https://www.phoenixcontact.com/in/products/3063167



Technical data

Product properties

Product type	Cable sleeve
No. of conductors	1

Material specifications

Material	Elastomer
Flammability rating according to UL 94	V0

Cable/line

External cable diameter	8 mm 9 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP54
Ambient temperature (operation)	-20 °C 80 °C

3063167

https://www.phoenixcontact.com/in/products/3063167



Classifications

ECLASS

ECLASS-11.0	27144425
ECLASS-13.0	27144425

3063167

https://www.phoenixcontact.com/in/products/3063167



Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in