

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 630 V, nominal current: 32 A, number of connections: 4, connection method: Screw connection, cross section: 0.5 mm² - 6 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: dark gray

Commercial data

Item number	3214204
Packing unit	1 pc
Minimum order quantity	50 pc
Sales key	BE1
Product key	BEK213
GTIN	4046356575317
Weight per piece (including packing)	14.206 g
Weight per piece (excluding packing)	8.749 g
Customs tariff number	39269098
Country of origin	IN

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Technical data

Product properties

Product type	Multi-conductor terminal block
Number of connections	4
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	0.77 W

Connection data

Number of connections per level	4
---------------------------------	---

Level 1 above 1+2 below 1+2

Screw thread	M3
Tightening torque	0.5 ... 0.6 Nm
Stripping length	8 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.5 mm ² ... 6 mm ²
Cross section AWG	20 ... 10 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 4 mm ²
Conductor cross section, flexible [AWG]	20 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 2.5 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 2.5 mm ²
Nominal current	32 A
Maximum load current	32 A (must not be exceeded by the total current)
Nominal voltage	630 V

Dimensions

Width	6.2 mm
End cover width	1.5 mm
Height	63.5 mm
Depth on NS 32	52 mm
Depth on NS 35/7,5	47 mm
Depth on NS 35/15	54.5 mm

Material specifications

Color	dark gray
Flammability rating according to UL 94	V2

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Insulating material group	I
Insulating material	PA
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Electrical tests

Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 4 mm ²	0.48 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.89 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 35
Test force setpoint	1 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.5 mm ² / 0.3 kg
	4 mm ² / 0.9 kg
	6 mm ² / 1.4 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
------------------	------

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Result	Test passed
Ambient conditions	
Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Drawings

Circuit diagram



TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/3214204>



EAC

Approval ID: RU C-DE.A*30.B.01742



cULus Recognized

Approval ID: E60425

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B	300 V	30 A	20 - 10	-
Use group C	300 V	30 A	20 - 10	-
Use group D	600 V	5 A	20 - 10	-

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

UNSPSC

UNSPSC 21.0	39121410
-------------	----------

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

Accessories

SCBI 10-6 - Fixed bridge

3246120

<https://www.phoenixcontact.com/in/products/3246120>

Fixed bridge, number of positions: 10, color: silver



INB 10-6 - Insertion bridge

3246188

<https://www.phoenixcontact.com/in/products/3246188>

Insertion bridge, Bridging in the terminal point, pitch: 6 mm, number of positions: 10, color: gray



TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

TS-TB-2L - Separating plate

3062841

<https://www.phoenixcontact.com/in/products/3062841>



Separating plate, for electrical isolation of neighboring bridges in the terminal center, depth: 14 mm, width: 0.5 mm, height: 16 mm, color: dark gray

TPS 3/10/4 - Test plug strip

3246230

<https://www.phoenixcontact.com/in/products/3246230>



Test plug strip, for 2.3 mm test plugs, for screwing into the bridge shaft, number of positions: 1, color: silver

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

SZS 0,6X3,5 VDE - Screwdriver

1212602

<https://www.phoenixcontact.com/in/products/1212602>



Screwdriver, slot-headed, VDE insulated, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

E/TB - End bracket

3246966

<https://www.phoenixcontact.com/in/products/3246966>



End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail

TB 4-QUATTRO EI - Feed-through terminal block

3214204

<https://www.phoenixcontact.com/in/products/3214204>



NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/in/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/in/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/in/products/0201744>



Test plug, with solder connection up to 1 mm² conductor cross section, number of positions: 1, color: gray

MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/in/products/0201663>

Insulating sleeve, color: white



TB 4-QUATTRO EI - Feed-through terminal block

3214204

<https://www.phoenixcontact.com/in/products/3214204>



MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/in/products/0201676>

Insulating sleeve, color: red



MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/in/products/0201689>

Insulating sleeve, color: blue



TB 4-QUATTRO EI - Feed-through terminal block

3214204

<https://www.phoenixcontact.com/in/products/3214204>

MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/in/products/0201692>

Insulating sleeve, color: yellow



MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/in/products/0201702>

Insulating sleeve, color: green



TB 4-QUATTRO EI - Feed-through terminal block



3214204

<https://www.phoenixcontact.com/in/products/3214204>

MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/in/products/0201728>

Insulating sleeve, color: gray



MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/in/products/0201731>

Insulating sleeve, color: black



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in