

CD-HF 60X100 - Cable duct

3240355

<https://www.phoenixcontact.com/in/products/3240355>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable duct for installation and mounting in control cabinets, light gray, halogen-free, comprising upper part and mounting base, width: 60 mm, height: 100 mm, length: 2000 mm

Your advantages

- Predetermined breaking point enables tool-free, burr-free removal of bars
- Thanks to its leverage and special cutting geometry, the PPS CD cable duct cutter enables easy, burr-free cutting with minimum effort
- Easy, burr-free cutting with minimum effort using the CUTFOX-CD cable duct cutter
- The wide, diagonal heads of the cable duct bars make it easy to fit the cover and hold it securely in place
- Installed conductors are securely held in place by means of wire retaining clips that can be snapped onto bars on the side
- Plastic body-bound rivets enable easy fixing of cable ducts using the rivet setting tool

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 3240355 |
| Packing unit | 8 pc |
| Minimum order quantity | 8 pc |
| Sales key | BE7 |
| Product key | BE7441 |
| Catalog page | Page 579 (C-3-2019) |
| GTIN | 4046356508407 |
| Weight per piece (including packing) | 1,500 g |
| Weight per piece (excluding packing) | 1,500 g |
| Customs tariff number | 39259020 |
| Country of origin | DE |

CD-HF 60X100 - Cable duct

3240355

<https://www.phoenixcontact.com/in/products/3240355>



Technical data


Product properties

| | |
|--------------|-------------|
| Product type | Wiring duct |
|--------------|-------------|

Connection data

| | |
|-----------------------|----------------------|
| Nominal cross section | 4239 mm ² |
|-----------------------|----------------------|

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 60 mm |
| Height | 2000 mm |
| Depth | 100 mm |
| Length | 2000 mm |

Material specifications

| | |
|--|---------------------|
| Color | light grey RAL 7035 |
| Material | PC/ABS |
| Flammability rating according to UL 94 | V0 |
| Components | halogen-free |

Cable/line

| | |
|--------------|-----|
| Halogen-free | yes |
|--------------|-----|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 90 °C |
|---------------------------------|------------------|

CD-HF 60X100 - Cable duct


3240355

<https://www.phoenixcontact.com/in/products/3240355>



Drawings

Dimensional drawing



Base perforation according to DIN EN 50085

CD-HF 60X100 - Cable duct



3240355

<https://www.phoenixcontact.com/in/products/3240355>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/3240355>



CSA

Approval ID: 248269



UL Recognized

Approval ID: FILE E 328576



VDE Zeichengenehmigung

Approval ID: 40028972



EAC

Approval ID: RU C-DE.PB68.W.00513

DNV

Approval ID: TAE00004VN

CD-HF 60X100 - Cable duct

3240355

<https://www.phoenixcontact.com/in/products/3240355>



Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27400703 |
| ECLASS-12.0 | 27400703 |
| ECLASS-13.0 | 27400703 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000012 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131700 |
|-------------|----------|

CD-HF 60X100 - Cable duct

3240355

<https://www.phoenixcontact.com/in/products/3240355>



Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

CD-HF 60X100 - Cable duct

3240355

<https://www.phoenixcontact.com/in/products/3240355>



Accessories

CD-HF COVER 60 - Cover profile

3240372

<https://www.phoenixcontact.com/in/products/3240372>



Cover for cable duct, light gray, halogen-free, width: 60 mm, length: 2000 mm

RVT-PA 4 - Fastening clip

3240498

<https://www.phoenixcontact.com/in/products/3240498>



Plastic body-bound rivet, for hole diameter of 4 mm and a material thickness of 1.5 ... 6 mm

CD-HF 60X100 - Cable duct

3240355

<https://www.phoenixcontact.com/in/products/3240355>



RVT-PA 6 - Fastening clip

3240499

<https://www.phoenixcontact.com/in/products/3240499>



Plastic body-bound rivet, for hole diameter of 6 mm and a material thickness of 1.5 ... 6 mm

UNIFOX-RVT P 4 - Tool

1212478

<https://www.phoenixcontact.com/in/products/1212478>



Rivet setting tool, for use with RVT-PA 4 plastic body-bound rivets

CD-HF 60X100 - Cable duct

3240355

<https://www.phoenixcontact.com/in/products/3240355>



UNIFOX-RVT P 6 - Tool

1212509

<https://www.phoenixcontact.com/in/products/1212509>



Rivet setting tool, for use with RVT-PA 6 plastic body-bound rivets

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in