

MM A MINI-IO CAB99 1.5m

772200



Adapter cable for PNOZmulti 2 and PSS 4000 Motion Monitoring, 1.5 m.

Technical details

| General data | |
|---------------------------------|------------------------------|
| Approval: | CE, UKCA |
| Technical data | |
| Environmental data | |
| Ambient temperature: | 0 - 60 °C |
| Condensation permitted?: | Not permitted |
| Mechanical data | |
| Connector type 1: | 8-pin Mini-IO male connector |
| Shape of connector type 1: | straight |
| Contact surfaces material 1: | Au |
| Length cable: | 1.5 m |
| Tolerance of cable length K1: | +/- 0.15 m |
| Colour cable insulation 1: | Green, similar to RAL6018 |
| Material of cable insulation 1: | PUR |
| Trailing capability of cable 1: | yes |
| Bend radius (when laying) K1: | 8 x Ø |
| Max. outside diameter cable K1: | 6 - 6 mm |
| Conductor cross section: | 0.14 - 0.14 mm ² |
| Shielding K1: | yes |
| Number of conductors: | 8 |

| | |
|--------------------------------|--------------------------------|
| Approvals for cable K1: | UL AWM-Style 20233 |
| Approvals for connector 1: | UL94 V-0 |
| Net weight: | 95 g |
| Gross weight: | 105 g |
| Environment | |
| RoHS directive: | 2011/65/EU, 2015/863/EU |
| RoHS conformity: | yes |
| RoHS exceptions: | yes |
| RoHS except.s acc. to direct.: | 6c |
| REACH compliance: | contains min. 1 SVHC-substance |
| REACH included substances: | Lead |
| %-part of the pollutant: | > 0,1 |
| CAS No.: | 7439-92-1 |
| WEEE classification (08/2018): | 5 devices (feed size < 50cm) |
| SCIP entry available: | 0 |
| Commercial data | |
| Harmonized System Code: | 85444290 |
| UNSPSC 25: | 26121603 |
| EAN-Code: | 4046548079111 |
| ECLASS version: | ECLASS-13 |
| ECLASS Reference Feature: | 27060313 |
| ETIM Version: | ETIM-9.0 |
| ETIM Reference Group: | EG000026 |
| ETIM Reference Feature: | EC001855 |
| Volume: | 0 dm3 |