

MM A MINI-IO CAB19 5m

772222



Motion Monitoring Adapter ELAU PACDRIVE3, 0.2/5 m.

Technical details

General data

Approval: CE, UKCA

Technical data

Environmental data

Ambient temperature: 0 - 60 °C

Condensation permitted?: Not permitted

Mechanical data

Connector type 1: 10-pin RJ45 female connector

Shape of connector type 1: straight

Connector type 2: 10-pin RJ45 male connector

Shape of connector type 2: straight

Connector type 3: 8-pin Mini-IO male connector

Shape of connector type 3: straight

Housing material connector 3: PBT

Contact surfaces material 1: Au

Contact surfaces material 2: Au

Contact surfaces material 3: Au

Cable material K1: Cu

Cable material K2: Cu

Length cable: 0.2 m

Tolerance of cable length K1:	+ 0.055m
Tolerance of cable length K2:	+/- 0.15 m
Category of cable K1:	Cat5
Colour cable insulation 1:	Green
Colour cable insulation 2:	Green
Housing colour:	Black RAL 9005
Material of cable insulation 1:	PUR
Material of cable insulation 2:	PUR
Trailing capability of cable 1:	yes
Trailing capability of cable 2:	Yes
Bend radius (when laying) K1:	10 x Ø
Bend radius (when laying) K2:	8 x Ø
Bend radius constant motion K2:	10 x Ø
Max. outside diameter cable K1:	7 - 7 mm
Conductor cross section:	0.14 - 0.14 mm ²
Diameter data line AWG K1:	26
Cross section data cable K1:	(4 x 2 x 0.14) mm ²
Cross section UB cable K1:	2 x 0.25 mm ²
Shielding K1:	yes
Shielding K2:	Yes
Separating layer bt. cores K2:	No
Number of conductors:	10
Approvals for cable K1:	UL AWM-Style 20963
Approvals for cable K2:	UL AWM-Style 20233
Approvals for connector 1:	UL94 V-0
Approvals for connector 2:	UL94 V-0
Approvals for connector 3:	UL94 V-0
Housing material:	TPE-SEBS UL 94 HB
Height dimension:	24.8 mm

Width dimension:	31 mm
Depth dimension:	85.2 mm
Net weight:	300 g
Gross weight:	315 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
SCIP entry available:	0
Commercial data	
Harmonized System Code:	85444290
UNSPSC 25:	26121603
EAN-Code:	4046548090468
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27060313
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC001855
Volume:	0 dm3