

Cable/XX/USB-ASM/MIN-BAMX/U/003/Q009/SH

772300



Connection lead, USB 2.0 Type A on USB 2.0 Type Mini-B, conductor cross section: 0.09 mm², shielded, cable length: 3 m

Technical details

| | |
|---------------------------------|-----------------------------|
| General data | |
| Approval: | CE, UKCA |
| Technical data | |
| Electrical data | |
| Rated current: | 0.5 A |
| Fieldbus interface | |
| Environmental data | |
| Ambient temperature: | -20 - 60 °C |
| Mechanical data | |
| Shape of connector type 1: | straight |
| Shape of connector type 2: | angled |
| Cable material K1: | Cu |
| Length cable: | 3 m |
| Housing colour: | Black |
| Material of cable insulation 1: | PVC |
| Trailing capability of cable 1: | no |
| Max. outside diameter cable K1: | 3.7 - 3.7 mm |
| Conductor cross section: | 0.09 - 0.09 mm ² |
| Cable cross section AWG K1: | 28 |
| Shielding K1: | yes |

| | |
|--------------------------------|------------------------------|
| Number of conductors: | 4 |
| Halogen-free: | yes |
| Net weight: | 61 g |
| Gross weight: | 68 g |
| Environment | |
| RoHS directive: | 2011/65/EU, 2015/863/EU |
| RoHS conformity: | yes |
| RoHS exceptions: | no |
| REACH compliance: | Contains no SVHC substances |
| WEEE classification (08/2018): | 5 devices (feed size < 50cm) |
| Commercial data | |
| Harmonized System Code: | 85444290 |
| UNSPSC 25: | 26121603 |
| EAN-Code: | 4046548107128 |
| ECLASS version: | ECLASS-13 |
| ECLASS Reference Feature: | 27060307 |
| ETIM Version: | ETIM-9.0 |
| ETIM Reference Group: | EG000001 |
| ETIM Reference Feature: | EC003249 |
| Volume: | 0.288 dm ³ |