

## PNOZ mc4p DeviceNet 2

773711



Configurable safe small controllers, PNOZmulti Classic, fieldbus module, DeviceNet.

### Technical details

#### General data

Approval: CE, UKCA, cULus Listed, KOSHA, EAC (Eurasian)

#### Technical data

#### Electrical data

Purpose of UINT1: Module supply

Source of internal voltage: Via base unit

Voltage type of UINT1: DC

Tolerance of UINT. Module: -2 %/+2 %

#### Fieldbus interface

Fieldbus interface: DeviceNet

Fieldbus device type: Slave

Perm. fieldbus station address: 0 ... 63d

Selectable transmission rates: 500 kBit/s, 250 kBit/s, 125 kBit/s

Connection fieldbus: 5-pin Combicon plug-in connect

Galv. isolation fieldbus: Yes

Test voltage: 500 V AC

#### Environmental data

Ambient temperature standard: EN 60068-2-14


Ambient temperature: 0 - 60 °C

Storage temperature standard: EN 60068-2-1/-2

Climatic suitability standard:	EN 60068-2-30, EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Not permitted
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61131-2
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	III
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
<b>Mechanical data</b>	
Mounting position:	horizontal on top hat rail
DIN-rail dimensions:	35 x 7.5 EN 50022
Housing material lower section:	PPO UL 94 V0
Housing material front plate:	ABS UL 94 V0
Height dimension:	94 mm
Width dimension:	22.5 mm
Depth dimension:	122 mm
Net weight:	110 g
Gross weight:	150 g
<b>Environment</b>	
WEEE classification (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
Harmonized System Code:	85389091
UNSPSC 25:	39122331
EAN-Code:	4046548064216
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27242208

ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC001423
Volume:	0.431 dm <sup>3</sup>

## Optional accessories



774639

KOP-XE