

PNOZ mc3p Profibus 2

773732



PNOZmulti Classic, communication module, standard, fieldbus, PROFIBUS-DP slave, station address 0 - 99, 1 D-Sub female connector 9-pin, transmission rates 9.6 kBit/s - 1 Mbit/s, 24/128 Bit virtual inputs, 24/128 Bit virtual outputs.

Technical details

General data	
Approval:	CE, UKCA, cULus Listed, KCC, KOSHA, EAC (Eurasian)
Technical data	
Electrical data	
Purpose of UINT1:	Module supply
Source of internal voltage:	Via base unit
Voltage type of UINT1:	DC
Tolerance of UINT. Module:	-2 %/+2 %
Fieldbus interface	
Fieldbus interface:	PROFIBUS-DP
Fieldbus device type:	Slave
Perm. fieldbus station address:	0 - 99d
Range fieldbus trans. rate:	9.6 kBit/s - 12 MBit/s
Connection fieldbus:	9-pin D-Sub female connector
Galv. isolation fieldbus:	Yes
Test voltage:	500 V AC
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	0 - 60 °C
Storage temperature standard:	EN 60068-2-1/-2

Climatic suitability standard:	EN 60068-2-30, EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Not permitted
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61131-2
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	III
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Mechanical data	
Mounting position:	horizontal on top hat rail
DIN-rail dimensions:	35 x 7.5 EN 50022
Housing material lower section:	PPO UL 94 V0
Housing material front plate:	ABS UL 94 V0
Height dimension:	94 mm
Width dimension:	22.5 mm
Depth dimension:	119 mm
Net weight:	119 g
Gross weight:	138 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85389091

UNSPSC 25:	39122331
EAN-Code:	4046548063400
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27242208
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC001423
Volume:	0.427 dm3

Optional accessories



774639

KOP-XE