

PNOZ msi13p Fanuc 20/20 2,5m

773869



Adapter cable speed monitor, RJ45 connector and 20-pin encoder connection, for PNOZ msXp and PNOZ s30, 2.5 m, for FANUC.

Technical details

General data	
Approval:	CE, UKCA
Technical data	
Environmental data	
Ambient temperature:	0 - 60 °C
Mechanical data	
Connector type 1:	20-pin D-Sub female connector
Connector type 2:	20-pin D-Sub male connector
Connector type 3:	8-pin RJ45 male connector
Shape of connector type 3:	straight
Housing material connector 3:	PBT
Cable material K2:	Cu
Cable type K1:	Li9YC11Y
Length cable:	2.5 m
Tolerance of cable length K1:	+/- 0.15 m
Colour cable insulation 1:	Green, similar to RAL6018
Housing colour:	Grey
Material of cable insulation 1:	PUR
Material of cable insulation 2:	PVC
Trailing capability of cable 1:	yes

Trailing capability of cable 2:	No
Bend radius (when laying) K1:	8 x Ø
Max. outside diameter cable K1:	6 - 6 mm
Conductor cross section:	0.14 - 0.14 mm ²
Shielding K1:	yes
Shielding K2:	Yes
Separating layer bt. cores K2:	No
Number of conductors:	8
Approvals for cable K1:	UL AWM-Style 20233
Approvals for connector 1:	UL94 V-0
Approvals for connector 2:	UL94 V-0
Approvals for connector 3:	UL94 V-0
Housing material:	ABS
Height dimension:	42 mm
Width dimension:	33.4 mm
Depth dimension:	13.5 mm
Net weight:	152 g
Gross weight:	164 g
Environment	
WEEE klassifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85444290
UNSPSC 25:	26121603
EAN-Code:	4046548025415
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27060313
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC001855

Volume:

0 dm³