

PNOZ mli1p 5m screw

773890



Cable for safe connection of 2 PNOZ ml1p, 5-pin shielded, plug-in screw terminals, 5 m.

Technical details

General data

Approval: cULus Listed

Technical data

Mechanical data

Connector type 1: 5-pin female connector

Connector type 2: 5-pin female connector

Contact surfaces material 1: Tin-plated

Material of sockets: Cu alloy

Length cable: 5 m

Colour cable insulation 1: Grey

Housing colour: Black RAL 9011

Trailing capability of cable 1: no

Shielding K1: yes

Number of conductors: 5

Approvals for connector 1: UL94 V-0

Approvals for connector 2: UL94 V-0

Height dimension: 22.6 mm

Width dimension: 17.5 mm

Depth dimension: 11.6 mm

Net weight: 167 g

| | |
|--------------------------------|--------------------------------|
| Gross weight: | 182 g |
| Environment | |
| RoHS directive: | 2011/65/EU, 2015/863/EU |
| RoHS conformity: | yes |
| RoHS exceptions: | yes |
| RoHS except.s acc. to direct.: | 6c |
| REACH compliance: | contains min. 1 SVHC-substance |
| REACH included substances: | Lead |
| %-part of the pollutant: | > 0,1 |
| CAS No.: | 7439-92-1 |
| WEEE klassifikation (08/2018): | 5 devices (feed size < 50cm) |
| SCIP entry available: | 0 |
| Commercial data | |
| Harmonized System Code: | 85444290 |
| UNSPSC 25: | 26121603 |
| EAN-Code: | 4046548050325 |
| ECLASS version: | ECLASS-13 |
| ECLASS Reference Feature: | 27060313 |
| ETIM Version: | ETIM-9.0 |
| ETIM Reference Group: | EG000026 |
| ETIM Reference Feature: | EC001855 |
| Volume: | 0 dm ³ |