

PNOZ mli1p 5m spring

773893



Cable for safe connection of 2 PNOZ ml1p, 5-pin shielded, spring-loaded terminal, 5 m.

Technical details

General data	
Approval:	cULus Listed
Technical data	
Mechanical data	
Connector type 1:	5-pin female connector
Connector type 2:	5-pin female connector
Contact surfaces material 1:	Tin-plated
Material of sockets:	Cu alloy
Length cable:	5 m
Colour cable insulation 1:	Grey
Housing colour:	Black RAL 9011
Trailing capability of cable 1:	no
Shielding K1:	yes
Number of conductors:	5
Approvals for connector 1:	UL94 V-0
Approvals for connector 2:	UL94 V-0
Height dimension:	22 mm
Width dimension:	17.5 mm
Depth dimension:	13 mm
Net weight:	145 g

Gross weight:	160 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
SCIP entry available:	0
Commercial data	
Harmonized System Code:	85444290
UNSPSC 25:	26121603
EAN-Code:	4046548050356
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27060313
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC001855
Volume:	0 dm ³