



## Field mounted HART temperature transmitter

### 7501

- RTD, TC, Ohm, and bipolar mV input and analog output
- High definition local operator interface (LOI) with 3 optical buttons
- Selectable red or white backlight
- Ex d explosion proof / flame proof in aluminum or 316 stainless steel version
- HART 7 functionality with HART 5 compatibility



#### High defintion display

- 0, 90, 180, & 270 degree position adjustments.
- Monitoring, programming and diagnostics view.
- Extensive diagnostics with flashing red or white backlight
- Supports 7 languages.

#### Local operator interface (LOI)

- 3 optical buttons; up, down and enter.
- Dynamically adaptive to wear or accumulation of dirt.
- Immune to interference from ambient light sources.
- Useable with or without gloves.

#### Configuration

- From the LOI through PR guided menu.
- PReset and HART modem.
- HHC, DCS or AMS via HART.

#### Mounting / installation

- For installation in zone 0, 1, 2 and zone 21, 22 and in Class 1, Division 1 and 2 applications.
- Hardware assessed for use in SIL applications.
- Mounting on 1.5"-2" pipe bracket or on wall / bulkhead.

#### Application

- Linearized temperature measurement with TC and RTD sensors e.g. Pt100 and Ni100.
- HART communication and 4...20 mA analog PV output for individual, difference or average temperature measurement of up to two RTD or TC input sensors.
- Conversion of linear resistance to a standard analog current signal, e.g. from valves or Ohmic level sensors.
- Amplification of bipolar mV signals to standard 4...20 mA current signals.
- Up to 63 transmitters (HART 7) can be connected in a multidrop communication setup.

#### Technical characteristics

- NAMUR NE43 and NE89.
- HART protocol revision can be changed by user configuration to either HART 5 or HART 7 protocol.

#### Applications


##### Input signals:

For full overview of input connections, refer to manual


RTD to 4...20 mA



TC to 4...20 mA




Resistance to 4...20 mA




mV to 4...20 mA



Difference or average  
RTD, TC or mV



2-wire output and HART:



Ex ia: 10...30 VDC  
(12...30 VDC with backlight)

Other: 10...35 VDC  
(12...35 VDC with backlight)

## Order

Type	Housing	Local operator interface		O-ring	Conduit thread (D1, D2 & D3)	Paint type	Transmitter	Approvals	Cover color	Additional approvals
		Optical buttons	Display							
7501	Low copper aluminum (AL) : A	No	No : 1	-40 to +85°C silicone rubber : A	M20x1.5 6H : 1	Epoxy : A	Yes : 1	General purpose : 1	Red : -	Marine : M
		No	Yes : 2	-20 to +85°C FKM rubber : B	½ NPT mod. : 2	Epoxy + polyurethane : B	No (comes with a connection kit) : 2	Hazardous area : 2		
		Yes	Yes : 3				Yes : 1	Hazardous area : 2	Gray : GY	
7501	316 Stainless steel (RF) : B	No	Yes : 2	-40 to +85°C silicone rubber : A	M20x1.5 6H : 1	None : N	Yes : 1	General purpose : 1	Steel : -	Marine : M
		Yes	Yes : 3	-20 to +85°C FKM rubber : B	½ NPT mod. : 2		No (comes with a connection kit) : 2	Hazardous area : 2		

## Environmental Conditions

Operating temperature.....	-40°C to +85°C (with silicone O-ring)
Operating temperature.....	-20°C to +85°C (with FKM O-ring)
Storage temperature.....	-40°C to +85°C
Calibration temperature.....	20...28°C
Relative humidity.....	0...100% RH (condensing)
Protection degree.....	IP54 / IP66 / IP68 / type 4X
Corrosion class 7501AxxxBxxxx / durability.....	C5-I/M / 5...15 years

## Mechanical specifications

Dimensions.....	Ø 110 mm
Dimensions (HxDxW), aluminum.....	109.3 x 145 x 126 mm
Dimensions (HxDxW), stainless steel.....	107.4 x 145 x 124 mm
Weight approx., aluminum / stainless steel.....	1.3 / 2.8 kg
Wire size.....	0.13 x 1.5 mm <sup>2</sup> / AWG 26...16 stranded wire
Screw terminal torque.....	0.4 Nm
Vibration.....	IEC 60068-2-6
2...25 Hz.....	±1.6 mm
25...100 Hz.....	±4 g
Display resolution.....	96 x 64 pixels
Number of digits.....	5
Backlight.....	Selectable ON/OFF
Backlight color.....	Selectable white or red

## Common specifications

### Supply

Supply voltage, DC: Ex ia, intrinsically safe.....	10 (12 - with backlight)...30 VDC
Supply voltage, DC: Other.....	10 (12 - with backlight)...35 VDC

### Isolation voltage

Isolation voltage, test / working.....	1.5 KVAC / 50 VAC
--	-------------------

### Response time

Response time (programmable).....	1...60 s
Signal / noise ratio.....	> 60 dB
Programming.....	HART
Start-up time, transmitter to display.....	Max. 5 s
Long-term stability, better than.....	±0.1% of span / year
Accuracy.....	Better than 0.05% of selected range
Signal dynamics, input.....	22 bit
Signal dynamics, output.....	16 bit
EMC immunity influence.....	< ±0.1% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst.....	< ±1% of span

## Input specifications

### Common input specifications

Max. offset.....	50% of selected max. value
------------------	----------------------------

### RTD input

RTD type.....	Pt50/100/200/500/1000; Ni50/100/120/1000
---------------	--

Cable resistance per wire.....	5 Ω (up to 50 Ω per wire is possible with reduced measurement accuracy)
--------------------------------	---

Sensor current.....	Nom. 0.2 mA
---------------------	-------------

### Linear resistance input

Linear resistance min....max.....	0 Ω...7000 Ω
-----------------------------------	--------------

### TC input

Thermocouple type.....	B, E, J, K, L, N, R, S, T, U, W3, W5, LR
------------------------	--

Cold junction compensation (CJC).....	Constant, internal or external via a Pt100 or Ni100 sensor
---------------------------------------	--

### Voltage input

Measurement range.....	-800...+800 mV
------------------------	----------------

Min. measurement range (span).....	2.5 mV
------------------------------------	--------

Input resistance.....	10 MΩ
-----------------------	-------

## Output specifications

### Current output

Signal range.....	4...20 mA
-------------------	-----------

Min. signal range.....	16 mA
------------------------	-------

Load (@ current output).....	≤ (Vsupply - 10) / 0.023 [Ω]
------------------------------	------------------------------

Load resistance, with backlight.....	≤ (Vsupply - 12) / 0.023 [Ω]
--------------------------------------	------------------------------

Sensor error indication.....	Programmable 3.5...23 mA
------------------------------	--------------------------

NAMUR NE43 Upscale/Downscale.....	23 mA / 3.5 mA
-----------------------------------	----------------

### Common output specifications

Updating time.....	440 ms
--------------------	--------

HART protocol revisions.....	HART 7 and HART 5
------------------------------	-------------------

## Observed authority requirements

EMC.....	2014/30/EU & UK SI 2016/1091
----------	------------------------------

ATEX.....	2014/34/EU & UK SI 2016/1107
-----------	------------------------------

RoHS.....	2011/65/EU & UK SI 2012/3032
-----------	------------------------------

EAC.....	TR-CU 020/2011
----------	----------------

EAC Ex.....	TR-CU 012/2011
-------------	----------------

## Approvals

ATEX.....	DEKRA 15ATEX0058X
-----------	-------------------

IECEx.....	IECEEx DEK 15.0039 X
------------	----------------------

c FM us.....	FM16US0009X / FM16CA0010X
--------------	---------------------------

CSA.....	70024231
----------	----------

INMETRO.....	DEKRA 15.0014 X
--------------	-----------------

NEPSI.....	GYJ20.1630X
------------	-------------

EU RO MR Type Approval.....	MRA0000009
-----------------------------	------------

EAC Ex.....	RU C-DK.HA65.B.00355/19
-------------	-------------------------

SIL.....	Hardware assessed for use in SIL applications
----------	---