



Figure similar

**Article No. :** 1FL6064-1AC61-2LB1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

|                      |                          |
|----------------------|--------------------------|
| Rated speed          | 2,000 rpm                |
| Rated torque (100 K) | 7.16 Nm                  |
| Rated current        | 4.6 A                    |
| Rated power          | 1.50 kW / 2.04 hp        |
| Max. speed           | 3,000 rpm                |
| Maximum torque       | 21.50 Nm                 |
| Max. current         | 13.8 A                   |
| Static torque        | 8.00 Nm                  |
| Moment of inertia    | 16.400 kgcm <sup>2</sup> |

### Physical constants

|                 |            |
|-----------------|------------|
| Torque constant | 1.60 Nm/A  |
| Thermal class   | B (130 °C) |
| Net weight      | 11.10 kg   |

### Ambient conditions

Ambient temperature

|           |             |
|-----------|-------------|
| Operation | 0 ... 40 °C |
|-----------|-------------|

Relative humidity

|                |  |
|----------------|--|
| Max. operation | 90 % RH maximum (no condensation at 30 °C) |
|----------------|--|

### Standards

|                           |         |
|---------------------------|---------|
| Compliance with standards | CE, EAC |
|---------------------------|---------|

### Mechanical data

|                          |   |
|--------------------------|---|
| Motor type               | High Inertia                                |
| Motor type               | Permanent-magnet synchronous motor          |
| Shaft height             | 65  |
| Encoder system           | Absolute encoder 20 bit + 12 bit multi-turn |
| Cooling                  | Natural cooling                             |
| Shaft end                | Feather key                                 |
| Radial runout tolerance  | Class N                                     |
| Vibration severity grade | Grade A                                     |
| Degree of protection     | IP65  |
| Design acc. to Code I    | IM B5 (IM V1, IM V3)                        |
| Connection type          | Angular connector (rotatable)               |

### Holding brake

|                          |              |
|--------------------------|--------------|
| Holding torque $M_{4Br}$ | 12.00 Nm     |
| Rated voltage            | 24 V DC 10 % |
| Opening time             | 180 ms       |
| Closing time             | 60 ms        |
| Rated current            | 1.50 A       |