



\*\*\* Spare part \*\*\* SIMATIC DP, Electronics module ET 200S 4AI standard I-2-wire, 4-20 mA; 13 bit, 15 mm width, for 2-wire transducer Cycle time 40 ms/module with SF LED (group fault)

General information	
Product function	
<ul style="list-style-type: none"> <li>• Isochronous mode</li> </ul>	No
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>• Rated value (DC)</li> <li>• Reverse polarity protection</li> </ul>	24 V; From power module Yes
Input current	
from load voltage L+ (without load), max.	125 mA
from backplane bus 3.3 V DC, max.	10 mA
output voltage / header	
supply voltage of the transmitters / header	
<ul style="list-style-type: none"> <li>• present</li> <li>• short-circuit proof</li> </ul>	Yes Yes; approx. 200 mA for module
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>• Address space per module, max.</li> </ul>	8 byte
Analog inputs	
Number of analog inputs	4
permissible input current for current input (destruction limit), max.	30 mA; limited electronically
Cycle time (all channels) max.	40 ms; 33 to 40 ms
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>• 4 mA to 20 mA</li> </ul>	Yes; Into 25 Ohm
Cable length	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	200 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> <li>• Integration time, parameterizable</li> <li>• Integration time (ms)</li> <li>• Interference voltage suppression for interference frequency f1 in Hz</li> </ul>	13 bit; 4 to 20 mA: 13 bit Yes 16,67 / 20 ms 50 / 60 Hz
Smoothing of measured values	
<ul style="list-style-type: none"> <li>• parameterizable</li> <li>• Step: None</li> <li>• Step: low</li> </ul>	Yes; in 4 stages Yes; 1x cycle time Yes; 4x cycle time

• Step: Medium	Yes; 16x cycle time
• Step: High	Yes; 32x cycle time
<b>Errors/accuracies</b>	
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.4 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.3 %
<b>Interrupts/diagnostics/status information</b>	
Diagnoses	
• Wire-break	Yes; Measuring range 1 to 5 V only
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
<b>Parameter</b>	
Remark	7 byte
Diagnostics wire break	1
Group diagnostics	1
Overflow/underflow	1
<b>Potential separation</b>	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	No
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>Dimensions</b>	
Width	15 mm
Height	81 mm
Depth	52 mm
<b>Weights</b>	
Weight, approx.	40 g

**last modified:** 5/22/2024 