

MLFB-Ordering data

6FC5370-3AM03-0AA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Rated data

Input voltage	DC 24 V +20 % -15 %
Power consumption, max.	50 W

### Mechanical data

Mounting position	Horizontal
Operator panel	Vertical
Net weight	3.00 kg (6.61 lb)
Width	420.0 mm (16.54 in)
Height	200.0 mm (7.87 in)
Depth	104.0 mm (4.09 in)

### Degree of protection

Front side	IP65 With the front flap closed
Rear side	IP20 / UL open type

### Panel cutout

Width	406.0 mm (15.98 in)
Height	186.0 mm (7.32 in)

### General tech. specifications

Mains buffering time	3 ms, 20 ms mit SITOP smart power supply
----------------------	--

### Ambient conditions

#### Ambient temperature

Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 50 °C (32 ... 122 °F)
Storage	-20 ... 60 °C (-4 ... 140 °F)
Transport	-20 ... 60 °C (-4 ... 140 °F)

#### Relative humidity

Operation	5 ... 90 %
Storage	5 ... 95 %
Transport	5 ... 95 %

### Approvals

Certificate of suitability	CE, EAC, KC
----------------------------	-------------