



Figure similar

### MLFB-Ordering data

6SL3210-5DE22-0UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Rated data

#### Input

Number of phases	3 AC
Line voltage	380 ... 480 V -15 % +10 %
Line frequency	45 ... 66 Hz

#### Output

Rated power	7.50 kW
Rated current (IN)	19.60 A
Max. output current	39.20 A

#### Electronic power supply

Power supply	24 V ±10 %
--------------	------------

### Connections

#### Motor end

Conductor cross-section	4.0 mm <sup>2</sup>
-------------------------	---------------------

### Mechanical data

Degree of protection	IP20 / UL open type
Frame size	FSC
Net weight	5.05 kg ( 11.13 lb )
Width	140.0 mm ( 5.51 in )
Height	260.0 mm ( 10.24 in )
Depth	240.0 mm ( 9.45 in )

### Ambient conditions

Cooling	Forced-air cooling via fan
Installation altitude	1000 m
Cooling air requirement	0.005 m <sup>3</sup> /s ( 0.177 ft <sup>3</sup> /s )

#### Ambient temperature

Operation	0 ... 45 °C ( 32 ... 113 °F )
Storage	-40 ... 70 °C ( -40 ... 158 °F )
Transport	-40 ... 70 °C ( -40 ... 158 °F )

#### Relative humidity

Max. operation	90 %
----------------	------

### Standards

Compliance with standards	CE
---------------------------	----