

Data Sheet | Item Number: 706-100/525-100

Connection cable; 25-pole; with solder pin; Male connector; open-ended; Length: 1 m; Conductor cross-section: 0.25 mm²

<https://www.wago.com/706-100/525-100>



Color coding acc. to DIN VDE 47100	25 pole male Sub-D connector
	Pole number
White	1
Brown	2
Green	3
Yellow	4
Grey	5
Pink	6
Blue	7
Red	8
Black	9
Violet	10
Grey-Pink	11
Red-Blue	12
White-Green	13
Brown-Green	14
White-Yellow	15
White-Brown	16
White-Grey	17
Grey-Brown	18
White-Pink	19
Pink-Brown	20
White-Blue	21
Brown-Blue	22
White-Red	23
Brown-Red	24
White-Black	25
Shield	Connected to Sub-D

Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Cable type	LiYCY
Color code	per DIN VDE 47100

Connection 1	
Connector	D-subminiature male connector
Pole number 1	25
Connection type 1	System
Wire cross-section	0.25 mm ²

Connection 2

Connector 2	open-ended
Connection type 2	open-ended

Physical data

Cable length	1 m
--------------	-----

Material data

Fire load	0 MJ
Weight	256 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4055143743884
Customs tariff number	85444290900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-100/525-100	
---	--