

# Data Sheet | Item Number: 706-100/625-400

Connection cable; 25-pole; with solder pin; Female connector; open-ended; Length: 4 m; Conductor cross-section: 0.25 mm<sup>2</sup>

<https://www.wago.com/706-100/625-400>



Color coding acc. to DIN VDE 47100	25 pole female Sub-D connector
	Pole number
White	1
Brown	2
Green	3
Yellow	4
Grey	5
Pink	6
Blue	7
Red	8
Black	9
Violet	10
Grey-Pink	11
Red-Blue	12
White-Green	13
Brown-Green	14
White-Yellow	15
Yellow-Brown	16
White-Grey	17
Grey-Brown	18
White-Pink	19
Pink-Brown	20
White-Blue	21
Brown-Blue	22
White-Red	23
Brown-Red	24
White-Black	25
Shield	Connect to Sub-D

## Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

## Electrical data

Operating voltage ≤ AC/DC 125 V  
Current per wire (max.) 2 A

## Connection data

Cable type LiYCY  
Color code per DIN VDE 47100

### Connection 1

Connector D-subminiature female connector  
Pole number 1 25  
Connection type 1 System  
Wire cross-section 0.25 mm<sup>2</sup>

### Connection 2

Connector 2 open-ended  
Connection type 2 open-ended

## Physical data

Cable length 4 m

### Material data

Fire load	0 MJ
Weight	770 g

### Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

### Commercial data

PU (SPU)	1 pcs
Country of origin	FR
GTIN	4066966236132
Customs tariff number	85444290900

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads

#### Environmental Product Compliance

##### Compliance Search

Environmental Product  
Compliance  
706-100/625-400

