

Data Sheet | Item Number: 706-150/326-100

Connection cable; 26-pole; Pluggable connector per DIN 41651; 26-pole; Pluggable connector per DIN 41651; Length: 1 m; Conductor cross-section: 0.14 mm²



<https://www.wago.com/706-150/326-100>



Similar to illustration

Color coding acc. to DIN VDE 47100	26 poles flat connector
	Pin number
White	1
Brown	2
Green	3
Yellow	4
Grey	5
Pink	6
Blue	7
Red	8
Black	9
Violet	10
Grey-Pink	11
Red-Blue	12
White-Green	13
Brown-Green	14
White-Yellow	15
White-Brown	16
White-Grey	17
Grey-Brown	18
White-Pink	19
Pink-Brown	20
White-Blue	21
Brown-Blue	22
White-Red	23
Brown-Red	24
White-Black	25
Brown-Black	26

Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Electrical data

Operating voltage ≤ AC/DC 35 V
Current per wire (max.) 1 A

Connection data

Cable type LiYY
Color code per DIN VDE 47100

Connection 1

Connector Pluggable connector per DIN 41651; female connector
Pole number 1 26
Connection type 1 System
Wire cross-section 0.25 mm²

Connection 2

Connector 2 Pluggable connector per DIN 41651; female connector
Pole number 2 26
Connection type 2 System

Physical data

Cable length	1 m
--------------	-----

Material data

Fire load	0 MJ
Weight	135 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4055143976732
Customs tariff number	85444290900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads**Environmental Product Compliance****Compliance Search**

Environmental Product
Compliance
706-150/326-100

