

Data Sheet | Item Number: 706-160/509-200

Connection cable; 9-pole; with solder pin; Male and female connector; 9-pole; D-subminiature; Length: 2 m; Conductor cross-section: 0.25 mm²



<https://www.wago.com/706-160/509-200>



Similar to illustration

Color coding acc. to DIN VDE 47100		9 poles male Sub-D connector	9 poles female Sub-D connector
		Pin number	Pin number
White		1	1
Brown		2	2
Green		3	3
Yellow		4	4
Grey		5	5
Pink		6	6
Blue		7	7
Red		8	8
Black		9	9
Shield		Connected to Sub-D	

Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Cable type	LiYCY
Color code	per DIN VDE 47100

Connection 1

Connector	D-subminiature male connector
Pole number 1	9
Connection type 1	System
Wire cross-section	0.25 mm ²

Connection 2

Connector 2	D-subminiature female connector
Pole number 2	9
Connection type 2	System

Physical data

Cable length	2 m
--------------	-----

Material data

Fire load	0 MJ
Weight	272 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4055143977050
Customs tariff number	85444290900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-160/509-200	
---	--