

# Data Sheet | Item Number: 706-3340/504-300

System cable; for Schneider Modicon M340; 8 analog outputs (current); Length: 3 m; Conductor cross-section: 0.25 mm<sup>2</sup>

<https://www.wago.com/706-3340/504-300>



Similar to illustration

Color coding acc. to DIN VDE 47100	25 pole Sub-D connector		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	NOV11.0	3	DI
Brown	2	NOV12.0	4	Com0
Green	3	NOV13.0	5	DI
Yellow	4	NOV14.0	6	Com1
Grey	5	NOV15.0	7	DI
Pink	6	NOV16.0	8	Com2
Blue	7	NOV17.0	9	DI
Red	8	NOV18.0	10	Com3
Black	9	NOV19.0	11	DI
Violet	10	NOV20.0	12	Com4
Grey-Pink	11	NOV21.0	13	DI
Red-Blue	12	NOV22.0	14	Com5
White-Green	13	NOV23.0	15	DI
Brown-Green	14	NOV24.0	16	Com6
White-Yellow	15	NOV25.0	17	DI
Yellow-Brown	16	NOV26.0	18	Com7
White-Grey	17	+24V	nc	nc
Grey-Brown	18	0V	nc	nc
White-Pink	19	+24V	nc	nc
Pink-Brown	20	0V	nc	nc
White-Blue	21	nc	nc	nc
Brown-Blue	22	nc	nc	nc
White-Red	23	nc	nc	nc
Brown-Red	24	1	nc	nc
White-Black	25	2	nc	nc
Shield				Connected to Sub-D

## Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

## Electrical data

Inputs/outputs	8 analog outputs; current
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

## Compatibility

### Schneider

Schneider Modicon M340 BMX AMO 0802

## Connection data

Cable type	LiYCY
Color code	per DIN VDE 47100

### Connection 1

Connector	D-subminiature female connector
Pole number 1	25
Connection type 1	System
Wire cross-section	0.25 mm <sup>2</sup>

### Connection 2

Connector 2	Schneider BMXFTB2020
Pole number 2	20
Connection type 2	System

### Physical data

Cable length	3 m
--------------	-----

### Material data

Fire load	0 MJ
Weight	360 g

### Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

### Commercial data

ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4055143432474
Customs tariff number	85444290900

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads


#### Environmental Product Compliance

##### Compliance Search

Environmental Product Compliance 706-3340/504-300	
--	---

### Documentation

#### System Description

WAGO System Wiring, Selection Guide	pdf 533.15 KB	
-------------------------------------	------------------	---