


Data Sheet | Item Number: 706-7753/304-100

System cable; for WAGO-I/O-SYSTEM, 750 Series; 2 x 8 analog inputs or outputs;

Length: 1 m; Conductor cross-section: 0.14 mm²

<https://www.wago.com/706-7753/304-100>



Similar to illustration

Color coding acc. to DIN VDE 47100 Cable 1; Channel 1-8	14 poles flat connector		20 poles flat connector	
	Pin number	Wiring	Pin number	Signal
White	1	CH1	1	DO1
Brown	2	CH2	2	DO2
Green	3	CH3	3	DO3
Yellow	4	CH4	4	DO4
Grey	5	CH5	5	DO5
Pink	6	CH6	6	DO6
Blue	7	CH7	7	DO7
Red	8	CH8	8	DO8
Black	9	+24V	17	+24V
Violet	10	0V	18	0V

Color coding acc. to DIN VDE 47100 Cable 2; Channel 9-16	14 poles flat connector		20 poles flat connector	
	Pin number	Wiring	Pin number	Signal
White	1	CH9	9	DO9
Brown	2	CH10	10	DO10
Green	3	CH11	11	DO11
Yellow	4	CH12	12	DO12
Grey	5	CH13	13	DO13
Pink	6	CH14	14	DO14
Blue	7	CH15	15	DO15
Red	8	CH16	16	DO16
Black	9	+24V	19	+24V
Violet	10	0V	20	0V

Short description:

WAGO's

interface cables provide fast and easy connection of WAGO's I/O modules equipped with a 20-pole pluggable connector. The following WAGO I/O Modules and Interface Adapters are compatible:

750-1500 (16 DO) --> 857-981 (DO)

750-1502 (8 DO/8 DI) --> 857-981 (DO) and 857-982 (DI)

The cables are available in 1-, 2- and 3-meter lengths; each has one 20-pole or two 14-pole pluggable connectors at both ends.

They are suitable for system wiring when paired with 857-981 and 857-982 Interface Adapters.

Notes

Note: When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Electrical data

Inputs/outputs	2 x 8 analog inputs or outputs
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1 A

Connection data

Cable type	LiYY	Connection 1	
Color code	per DIN VDE 47100	Connector	Pluggable connector per DIN 41651; female connector
		Pole number 1	20
		Connection type 1	System
		Wire cross-section	0.14 mm ²

Connection 2

Connector 2	Pluggable connector per DIN 41651; female connector
Pole number 2	14
Connection type 2	System

Connection 3

Connector 3	Pluggable connector per DIN 41651; female connector
Pole number 3	14
Connection type 3	System

Physical data

Cable length	1 m
--------------	-----

Material data

Fire load	0 MJ
Weight	97 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

Product Group	30 (WAGO France)
eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	FR
GTIN	4050821034209
Customs tariff number	85444290900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
706-7753/304-100



Documentation

System Description

WAGO System Wiring, Selection Guide

pdf
533.15 KB



Bid Text

706-7753/304-100

26.11.2018

docx
15.25 KB



706-7753/304-100

19.02.2019

xml
3.70 KB



CAD/CAE-Data

CAE data

WSCAD Universe
706-7753/304-100



1 Compatible Products

1.1 Optional Accessories

1.1.1 Interface module

1.1.1.1 Interface adapters



Item No.: 857-981

Interface adapter; 14-pole; High-side switching input

Item No.: 857-982

Interface adapter; 14-pole; High-side switching output