



Dimensions in mm

Technical data

Connection type	M12 plug
Pole number	4
Cable connection direction to mating direction	90°
Connector interface coding (cable/adapter) 1 1	A-coded
Contact resistance	≤3 mΩ

Connection data

Connection type 1	Screw clamp technology
Solid conductor	0.25 ... 0.75 mm ²

Mechanical data

Connectable sheathed cable diameter	4 ... 6 mm
Housing material	Polybutylene terephthalate (PBT)
Contact material	CuZn
Contact plating	Gold
Dichtungsmaterial	Sealing ring: neoprene
Mating cycles (max.)	100
Weight	26 g

Environmental requirements

Ambient temperature (operation)	-25 ... +85 °C
Protection type	IP67
Note on protection type	in locked state
Pollution degree	3
Fire load	0 MJ

Commercial data

eCl@ss 10.0	27-24-26-92
eCl@ss 9.0	27-24-26-92
ETIM 8.0	EC002584
ETIM 7.0	EC002584
PU (SPU)	5 pcs
Packaging type	Box
Country of origin	HU
GTIN	4044918977432
Customs tariff number	85366990990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 756-9204/040-000	↓

Documentation

System Description		Bid Text			
IP67 Cables and Plug-gable Connectors	pdf 157.80 KB	756-9204/040-000	19.02.2019	xml 2.69 KB	↓
		756-9204/040-000	20.09.2017	doc 24.00 KB	↓

CAD/CAE-Data

CAE data	
WSCAD Universe 756-9204/040-000	↓

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com