



Similar to illustration

Technical data

| | |
|--|------------|
| Connection type | M23 socket |
| Pole number | 6 |
| Cable connection direction to mating direction | 0 ° |

Connection data

| | |
|-------------------|----------------------|
| Connection type 1 | Soldering technology |
| Solid conductor | 2.5 mm ² |

Mechanical data

| | |
|-------------------------------------|-----------------|
| Connectable sheathed cable diameter | 6.5 ... 10.5 mm |
| Weight | 72.7 g |

Environmental requirements

| | |
|-----------------|------|
| Protection type | IP67 |
| Fire load | 0 MJ |

Commercial data

| | |
|-----------------------|----------------------------------|
| Product Group | 23 (I/O passive and accessories) |
| eCl@ss 10.0 | 27-24-26-92 |
| eCl@ss 9.0 | 27-24-26-92 |
| ETIM 8.0 | EC002584 |
| ETIM 7.0 | EC002584 |
| PU (SPU) | 1 pcs |
| Packaging type | Bag |
| Country of origin | DE |
| GTIN | 4045454434809 |
| Customs tariff number | 85366990990 |

Environmental Product Compliance

RoHS Compliance Status

Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance
756-9603/060-000



CAD/CAE-Data

CAE data

WSCAD Universe
756-9603/060-000

