


## Data Sheet | Item Number: 787-821

Switched-mode power supply; Pro; 1-phase; 12 VDC output voltage; 10 A output current; TopBoost + PowerBoost; DC OK contact

<https://www.wago.com/787-821>



### Features:

- Switched-mode power supply with PowerBoost and TopBoost
- Switch off the output and minimize power consumption via stand-by input
- Output monitoring via DC OK contact
- Suitable for both parallel and series operation
- Natural convection cooling when horizontally mounted
- Encapsulated for use in control cabinets
- Electrically isolated output voltage (SELV) per UL 60950-1; PELV per EN 60204

### Technical data

Input		Output	
Phases	1	Nominal output voltage $U_{o, nom}$	DC 12 V (SELV)
Nominal input voltage $U_{i, nom}$	1 x AC 100 ... 240 V	Output voltage range	DC 11 ... 18 V (adjustable)
Input voltage range	1 x AC 85 ... 264 V; DC 120 ... 300 V	Default setting	DC 12 V
Input voltage derating	-5 %/V (< 95 VAC)	Nominal output current $I_{o, nom}$	10 A (12 VDC)
Nominal mains frequency range	50 ... 60 Hz; 0 Hz	Nominal output power	120 W
Input current $I_i$	$\leq 0.97$ A (240 VAC; 10 ADC)	Deviation	$\leq 1$ %
Discharge current	$\leq 1$ mA	Residual ripple	$\leq 70$ mV (peak-to-peak)
Inrush current	$\leq 30$ A (peak)	Current limitation	$1.1 \times I_{o, nom}$ (typ.)
Power factor correction (PFC)	passive	Overload behavior	TopBoost/PowerBoost/Constant current mode
Mains failure hold-up time	$\geq 35$ ms (230 VAC)	PowerBoost	DC 20 A (4 s); DC 15 A (8 s)
		TopBoost	DC 60 A (25 ms); DC 40 A (25 ms; $U_i$

### Signaling and communication

Signaling	1 x LED DC OK (green) 1 x Error LED (red) 1 x Stand-by input 1 x DC OK relay contact (changeover contact)
Operation status indicator	Green LED (DC OK) Red LED (error)

### Efficiency/power losses

Power loss $P_i$	$\leq 0.5$ W (standby); $\leq 5$ W (no load); $\leq 14.6$ W (nominal load)
Efficiency (typ.)	87.8 %

### Circuit protection

Internal fuse	T 4 A / 250 VAC
Backup fusing (required)	An external DC fuse is required for the DC input voltage.
Backup fusing (recommended)	Circuit breaker: 6 A, 10 A, 16 A; Tripping characteristic: B or C

### Safety and protection

Isolation voltage (pri.-sec.)	DC 4.242 kV
Isolation voltage (pri.-PE)	DC 2.2 kV
Isolation voltage (sec.-PE)	DC 0.7 kV
Protection class	I
Protection type	IP20; per EN 60529
Resistance to reverse feed	≤ DC 25 V
Overvoltage category	II
Pollution degree	2
Transient suppression (primary)	Varistor
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	> 500,000 h (per IEC 61709)

### Connection data

Connection type 1	Input/output
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 231 Series
Solid conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches
Connection type 2	Signaling
Connection technology 2	CAGE CLAMP®
WAGO connector 2	WAGO 733 Series
Solid conductor 2	0.08 ... 0.5 mm <sup>2</sup> / 28 ... 20 AWG
Fine-stranded conductor 2	0.08 ... 0.5 mm <sup>2</sup> / 28 ... 20 AWG
Strip length 2	5 ... 6 mm / 0.2 ... 0.24 inches

### Physical data

Width	57 mm / 2.244 inches
Height	163 mm / 6.417 inches
Depth from upper-edge of DIN-rail	163 mm / 6.417 inches
Note (dimensions)	Height with connector

### Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

### Material data

Fire load	0 MJ
Weight	1295 g

### Environmental requirements

Ambient temperature (operation)	-25 ... +70 °C (Device starts at -40 °C (type-tested))
Ambient temperature (storage)	-25 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	-3 %/K (> 50 °C)

### Standards and specifications

Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 EN 61558-2-16 UL 60950 UL 508

### Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 8.0	EC002540
ETIM 7.0	EC002540
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821226482
Customs tariff number	85044083900

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Approvals / Certificates

#### General approvals



Approval	Standard	Certificate Name
EAC Brjansker Zertifizierungs- stelle	TP TC 004/2011, TP TC 020/2011	EAC RU C-DE.AM02. B.00089_19
UL Underwriters Laboratories Inc.	UL 508	E255817
UL Underwriters Laboratories Inc.	UL 60950-1	E255815

#### Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

### Downloads

#### Environmental Product Compliance

Compliance Search			
Environmental Product Compliance 787-821			↓

## Documentation

Bid Text			
787-821	04.07.2019	docx 20.39 KB	↓
787-821	04.07.2019	xml 7.53 KB	↓

Instruction Leaflet		
Primär getaktete Stromversorgungen PRO	pdf 247.20 KB	↓

## CAD/CAE-Data

CAD data	
2D/3D Models 787-821	↓

CAE data	
EPLAN Data Portal 787-821	↓
WSCAD Universe 787-821	↓
ZUKEN Portal 787-821	↓

## Engineering-Software

Configuration and Commissioning Software			
WAGO Line Length Calculation	1.3.5 09.12.2019	exe 329.50 KB	↓

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Marking

##### 1.1.1.1 Marking strip



**Item No.: 2009-110**  
Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

**Item No.: 210-831**  
Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white

**Item No.: 210-832**  
Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white

#### 1.1.2 Mounting adapter

### 1.1.2.1 DIN-rail adapter



**Item No.: 787-897**

Carrier rail adapter made of zinc die-cast; for mounting 787-8xx devices to a DIN 35 rail

**Item No.: 787-896**

Carrier rail adapter; for mounting 787-8xx devices to a DIN 35 rail

### 1.1.2.2 Wall-mount adapter



**Item No.: 787-895**

Mounting carrier; for screw fixing of 787-8xx devices on mounting plate or wall without DIN 35 rail

### 1.1.3 Tool

#### 1.1.3.1 Operating tool



**Item No.: 210-719**

Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft



**Item No.: 210-720**

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured



**Item No.: 210-769**

SCREWDRIVER; green