

WKM 18/43

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The halogen-free, transparent pocket of the WKM offers outstanding protection against environmental influences. Thanks to firm fixation with cable ties, it is suitable for almost all wire cross-sections.

The pre-printed tags are simply inserted into the WKM holder and secured with a clip. WKM cable markers are the right solution for maximum efficiency in on-site marking.

Your advantage when using WKM cables

- Paper and polyester labels can be printed individually with conventional office printers
- The robust design in combination with MultiCard ELS tags guarantees maximum protection against environmental influences

General ordering data

| | |
|------------|---|
| Version | WKM, Conductor and cable markers, 7 - 115 mm, 43 x 18 mm, Wire and cable markers, Transparent |
| Order No. | 1610700000 |
| Type | WKM 18/43 |
| GTIN (EAN) | 4008190204488 |
| Qty. | 50 Stück |

WKM 18/43

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technische Daten

Dimensions and weights

| | | | |
|------------|--------|-----------------|------------|
| Depth | 3.5 mm | Depth (inches) | 0.138 inch |
| Height | 43 mm | Height (inches) | 1.693 inch |
| Width | 18 mm | Width (inches) | 0.709 inch |
| Net weight | 1.66 g | | |

Temperatures

| | |
|-----------------------------|-------------|
| Operating temperature range | -40...80 °C |
|-----------------------------|-------------|

General data

| | | | |
|--------------------------------------|---|-----------|--|
| Application/manufacture | Wire and cable markers | | |
| Colour | Transparent | | |
| Material | Polypropylene | | |
| Number of markers per combination | 1 MultiCard = Conductor and cable markers | | |
| Number of markers per packaging unit | Form of supply | MultiCard | |
| Operating temperature range | -40...80 °C | | |
| Operating temperature range, max. | 80 °C | | |
| Operating temperature range, min. | -40 °C | | |
| Type of printing | neutral | | |
| UL 94 flammability rating | HB | | |
| Width | 18 mm | | |

Conductor and cable markers

| | | | |
|-------------------------------|--------------------|----------------------------------|--------------------------|
| Conductor O.D. | 7 - 115 mm | Conductor O.D., max. | 115 mm |
| Conductor O.D., min. | 7 mm | Conductor cross-section, max. | 150 mm ² |
| Conductor cross-section, min. | 16 mm ² | Cross-section for connected wire | 16 - 150 mm ² |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ECLASS 9.0 | 27-40-04-01 | ECLASS 9.1 | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |
| ECLASS 12.0 | 27-28-11-02 | ECLASS 13.0 | 27-28-11-02 |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| REACH SVHC | / |
| RoHS Compliance Status | Compliant without exemption |

Important note

| | |
|---------------------|--|
| Product information | For cable ties with a width up to 8.4 mm |
|---------------------|--|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

WKM 18/43

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technische Daten

Downloads

| | |
|------------------|--|
| Engineering Data | CAD data – STEP |
| Engineering Data | Zuken E3.S |
| Catalogues | Catalogues in PDF-format |

Datenblatt

WKM 18/43

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Zeichnungen

Example of use

